

Besinci sütunda Q ile gösterilen ürünler için yanlarında yazılı miktar kadar tarife kontenjanı açılması talep edilmiştir. S ile gösterilenler ise askıya alınması talep edilen ürünlerdir.

Söz konusu taleplere itiraz edecek firmaların GTP bazında değil tanım bazında başvuruları incelemeleri gerekmektedir.

EXDA4/LX40-04-30

BXL, 0412-04.2016 (12.0)

CYCLE 2017-01

List of new items—first second version

Sorting order

A—first **listings**, then 'suspensions'

B—CN code

C—**new requests**, **amending requests**

>>DISCLAIMER: The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group. Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic. <<

CN code	TARIC	Ref Mail	Description	S/Q
2002 90 31		1340131/2016	Tomato paste: — Of the genus <i>Solanum lycopersicum</i> — With a brix value of 27 or more but not more than 29 — With a dry matter content of 12% or more but not more than 31.73% by weight — With a temperature at break of 98C or more but not more than 100C — With a viscosity of not more than 3 cm (using the Bostwick test method) — In immediate packaging of a net content of 1.200 kgs or more — Made of tomato varieties having a thin pulp juice Bostwick lower than 12 cm and a Serum viscosity higher than 10.0 centistokes	Q/45000kg
2905 12 00		1337816/2016	Propan-1-ol (propyl alcohol) (CAS RN 71-23-8)	Q/12000tonnes
2909 49 80		1248500/2016	2,2,2',2'-tetrakis(hydroxymethyl)-3,3'-oxydipropan-1-ol (CAS RN 126-58-9)	Q/200tonnes

Biçimlendirilmiş Yazı tipi: 11 nk

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
2928 00 90		1279830/2016	Monomethylhydrazine (CAS 60-34-4) in form of an aqueous solution with a content by weight of monomethylhydrazine of 40 (± 5) %	Q/tonnes,
2935 00 90		1725576/2016	(3R,5S,E)-7-(4-(4-(1-butyl-7-(4-(4-fluorophenyl)-6-iso-propyl-2-N-methylmethylsulphonamido)pyrimidin-5-yl)-3,5-dihydroxhept-6-enoat	Q/5000kg, 01.01-31.12
3204 17 00		1349304/2016	Colourant C.I. Pigment Yellow 74 (CAS RN 6358-31-2) and preparations based thereon with a Colourant C.I. Pigment Yellow 74 content of 80 % or more by weight)	Q/350000kg, 01.01-31.12
3204 17 00		1349240/2016	Colourant C.I. Pigment Red 122 (CAS RN 980-26-7) and preparations based thereon with a Colourant C.I. Pigment Red 122 content of 80 % or more by weight)	Q/210000kg,
3204 17 00		1349348/2016	Colourant C.I. Pigment Red 2 (CAS RN 6041-94-7) and preparations based thereon with a Colourant C.I. Pigment Red 2 content of 80 % or more by weight)	Q/379000kg, 01.01-31.12
3204 17 00		1349274/2016	Colourant C.I. Pigment Violet 23 (CAS RN 6358-30-1) and preparations based thereon with a Colourant C.I. Pigment Violet 23 content of 80 % or more by weight)	Q/26000kg,
3901 00 00		1531096/2016	Polyethylene	Q/838000tonnes,
3902 00 00		1531355/2016	Polypropylene	Q/973000tonnes, 01.01-31.12
3902 20 00		1124358/2016	High Reactivity Polyisobutylene, with average molecular weight (Mn) 975 or more and equal or less than 2 500	Q/10000tonnes, 01.01-31.12
5504 10 00		1249699/2016	Staple fibres of viscose rayon [not carded, combed or otherwise processed for spinning], measuring 1,15 decitex or more, but not more than 1,3 decitex and having a fibre length of 36 mm or more, but not more than 38 mm	Q/8000tonnes,

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
5504 10 00		1367832/2016	Artificial staple fibres of viscose rayon not carded, combed or otherwise processed for spinning	Q/300000tonnes,
7019 40 00 7019 52 00		1290020/2016	Glasgewebe: — aus E-Glasfilamenten — (geliefert) in Rollen, mit einer Breite von 60,0 cm oder mehr, aber nicht mehr als 160,0 cm, — mit einer Glasgewebedicke von 0,020 mm oder mehr, aber nicht mehr als 0,260 mm, — mit einem Flächengewicht von 15 g/m² oder mehr, aber nicht mehr als 220 g/m²	Q/12180000 m, 01.01-31.12
ex 2825 30 0 0	10	0218/00/1998	Vanadium oxides and hydroxides exclusively for use in alloys	Q/200001, 01.01-31.12
ex 2915 21 0 0	10	136718/2010	Acetic acid of a purity by weight of 99 % or more (CAS RN 64-19-7)	Q/1000000tonnes, 1.1.-31.12.
2915 32 00		726215/2014 825537/2014 838627/2014 838774/2014 898981/2014	Vinyl acetate (CAS RN 108-05-4)	Q/200000tonnes, 01.01-31.12
ex 2916 19 9 5	20	314731/2011	Potassium (F.E)-hexa-2,4-dienoate (CAS RN 24634-61-5)	Q/8250tonnes, 01.01-31.12

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 2918 29 0 0	55	2989075/2014	<p>(...) for use in the manufacture of polymer- processing stabilizer-one packs based on powder mixtures --- UK - Mar 2016 ---</p> <p>Octadecyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate (CAS RN 2082-79- 3) with • a sieve passing fraction at a mesh width of 500 µm of more than 99 % by weight and • a melting point of 49 °C or more, but not more than 54 °C, for use in the manufacture of PVC-processing stabilizer-one packs based on powder mixtures (powders or press granulates) --- AT proposal 10.03.2016 ---</p> <p>Octadecyl 3-(3,5-di-tert-butyl-4- hydroxyphenyl)propionate (CAS RN 2082-79- 3) with — a sieve passing fraction at a mesh width of 500 µm of more than 99 % by weight and — a melting point of 110 °C or more, but not more than 125 °C, for use in the manufacture of PVC-processing stabilizer-one packs based on powder mixtures (1)</p>	Q/80tonnes, 01.01-31.12

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 2918 29 00	65	2989098/2014	(...) for use in the manufacture of polymer-processing stabilizer-one packs based on powder mixtures --- UK - Mar 2016 --- Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8) - with a sieve passing fraction at a mesh width of 250 µm of more than 75 % by weight and at a mesh width of 500 µm of more than 99 % by weight, and - a melting point of 110 °C or more, but not more than 125 °C, for use in the manufacture of PVC-processing stabilizer-one packs based on powder mixtures (powders or press granulates) --- AT proposal 10.03.2016 --- Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8) --- with a sieve passing fraction at a mesh width of 250 µm of more than 75 % by weight and at a mesh width of 500 µm of more than 99 % by weight, and --- a melting point of 49 °C or more, but not more than 54 °C, for use in the manufacture of PVC-processing stabilizer-one packs based on powder mixtures (1)	Q/380tonnes , 01.01-31.12
2926 10 00		910/2006	Acrylonitrile (CAS RN 107-13-1)	Q/17500tonnes , 01.01-31.12
ex 2930 90 99	28	3672624/2015	Flubendiamide (ISO) (CAS RN 272451-65-7)	Q/100tonnes , 01.07-31.12
ex 2932 99 00	40	3114/1/04	1,3:2,4-bis-O-(3,4-dimethylbenzylidene)- D-sorbitol (CAS RN 135861-56-2) UK proposal 14.03.2016 1,3:2,4-Bis-O-(3,4-dimethylbenzylidene)-D-glucitol (CAS RN 135861-56-2)	Q/500tonnes , 01.01-31.12

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
3905 30 00		3938957/2015	TR proposal 7.12.15: Poly(vinyl alcohol) (CAS RN 25213-24-5), whether or not containing unhydrolysed acetate groups Partially hydrolyzed polyvinyl alcohol (CAS RN 25213-24-5)	Q/3500tonne s, 01.07- 31.12
3905 30 00		137255/2010	Poly(vinyl alcohol), whether or not containing unhydrolysed acetate groups	Q/15000tonn es, 01.01- 31.12
7606 12 92 7607 11 90		1163/2007	Aluminium and magnesium alloy strip or foil: — in rolls, — of a thickness of 0,14 mm or more but not more than 0,27 mm, — a width of 12,5 mm, 15,0 mm, 16,0 mm, 25,0 mm, 35,0 mm, 50 mm or 356 mm, — a tensile strength of 285 N/mm2 or more, and — an elongation at break of 1 % or more, and — containing by weight: — 93,3 % or more of aluminium, — 0,8 % or more but not more than 5 % of magnesium, and — not more than 1,8 % of other elements	Q/500tonnes , 01.01-30.06
2009 81 95		1248211/2016	Juice of fruit of the species a Vaccinium macrocarpon — of a Brix value of 7 or more, but not more than 11 — not containing added sugar — in immediate packings of a net content of 200 litres or more for use in the manufacture of products of drink industry (1)	S
ex 2818 30 0 0	10	1242588/2016	Aluminum hydroxide: Aluminum hydroxide (trade name Catapal B)	S
2825 70 00		1242450/2016	Molybdate oxides and hydroxides: molybdenum trioxide containing a minimum of 66.5 % molybdenum	S

CN code	TARIC	Ref Mail	Description	S/Q
2825 90 85		1248342/2016	Diniobium pentaoxide (CAS-RN 1313-96-8) with a purity by weight of 99 % or more	S
2825 90 85		1248414/2016	Ditantalum pentaoxide (CAS RN 1314-61-0) with a purity by weight of 99 % or more	S
ex 2841 70 0 0	90	1242523/2016	Molybdenum: Diammonium Dimolybdate containing a minimum of 56 % molybdenum	S
2842 10 00		1345815/2016	Zeolite of a pore size of not more than 5 angstroms (CAS RN 1318-02-1)	S
2905 11 00		1338499/2016	Methyl methanesulphonate (CAS RN 66-27-3)	S
2909 19 90		1362862/2016	Sodium 2-[(2-(2-tridecoxyethoxy)ethoxy)ethyl] sulphate (CAS RN 25446-78-0) with a content by weight in water of 62 % or more but not more than 65 %	S
2909 30 90		1248461/2016	O,O,O-1,3,5-trimethylresorcinol (CAS RN 621-23-8)	S
2909 30 90		1338664/2016	Oxyfluorfen technical	S
2912 29 00		1174458/2016	Mixture of isomers 4-Isobutyl-2-methylbenzaldehyde and 4-methyl-2-isobutylbenzaldehyde in approximate proportion 85:15	S
2912 29 00		1174482/2016	2,6,6-trimethylcyclohexecarbaldehyde (alpha-beta isomers mixture; 45-55 % : 40-50 %)	S
2914 39 00		1338555/2016	1,4' Bis (4-Fluorobenzoyl) Benzene (CAS RN 68418-51-9)	S
2914 50 00		1338600/2016	4,4- Dihydroxybenzophenone (CAS RN 611-99-4)	S
2914 70 00		1338756/2016	4,4'-Difluorobenzophenone	S
2916 20 00		1279605/2016	Transfluthrin (ISO) (CAS RN 118712-89-3)	S
2918 30 00		1336330/2016	methyl benzoylformate (CAS RN 15206-55-0)	S

CN code	TARIC	Ref Mail	Description	S/Q
ex 2918 99 90	90	1242672/2016	4,5-Dihydroxy-9,10-dioxo-9,10-dihydroanthracene-2-carboxylic acid	S
2920 90 85		1279693/2016	Fosethyl-sodium (CAS RN 39148-16-8) in form of an aqueous solution with a content by weight of fosethyl-sodium of 35 % or more but not more than 45 %	S
2921 19 99		1362726/2016	2-Chloro-N-(2-chloroethyl)ethanamine hydrochloride (CAS RN 821-48-7)	S
2922 29 00		1279635/2016	Tris(4-aminophenyl) thiophosphate (CAS RN 52664-35-4)	S
2922 49 85		1174545/2016	Acid 2- (3-amino-4-chlorobenzoyl) benzoic OR (2- (3-Amino-4-chloro-benzoyl) benzoic acid) OR Cabba	S
2922 50 00		1275028/2016	2-(2-(2-aminoethoxy)ethoxy)acetic acid hydrochloride (CAS RN 134979-01-4)	S
2923 90 00		1338852/2016	Tetrabutylammonium bromide (CAS RN 1643-10-2)	S
2924 19 00		1336385/2016	2-propyryl butylcarbamate	S
2924 29 98		1249517/2016	3-Chloro-N-methoxy-N-methylpropanamide (CAS RN 1062512-53-1)	S
2926 90 95		1174566/2016	2-(4-cyanophenylamino)acetic acid—OR Nitrile-function compounds	S
2926 90 95		1279741/2016	4-Cyano-2-methoxybenzaldehyde (CAS RN 21962-45-8)	S
2928 00 90		1242892/2016	Pentan-2-one oxime (CAS RN 623-40-5)	S
2930 90 99		1362547/2016	N-(cyclohexylthio)phthalimide (CAS RN 17796-82-6)	S
2930 90 99		1338796/2016	Diphenyl sulphone (CAS RN 127-63-09)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
2930 90 99		1362812/2016	1-Hydrazino-3-(methylthio)propan-2-ol (CAS RN 14359-97-8)	S
2930 90 99		1279784/2016	2-Methyl-1-(methylthio)-2-propanamine (CAS RN 36567-04-1)	S
2933 39 99		1150602/2016	3,5-Dichloro-2-cyanopyridine	S
2933 39 99		1338889/2016	Pyridine-2,6-dicarboxylic acid (CAS RN 499-83-2)	S
2933 49 90		1345853/2016	Cloquintocet-mexyl (CAS RN 99607-70-2)	S
2933 59 95		1242965/2016	6-Benzyladenine (CAS RN 1214-39-7)	S
2933 59 95		1242932/2016	Diquat dibromide (ISO) (CAS RN 85-00-7) in aqueous solution	S
2933 59 95		1362772/2016	5-Bromo-2,4-dichloropyrimidine (CAS RN 36082-50-5)	S
2933 79 00		1099897/2016	Ethyl N-(tert-Butoxycarbonyl)-L-pyroglytamate (CAS RN 144978-12-1)	S
2933 99 80		1099939/2016	O-(benzotriazol-1-yl)-n,n,n',n'-tetramethyluronium tetrafluoroborate (CAR RN 125700-67-6)	S
2933 99 80		1092596/2016	3-chloro-2-(1,1-difluorobut-3-enyl)-6-methoxyquinoxaline (CAS RN 1799733-46-2)	S
2933 99 80		1279983/2016	(4aS,7aS)-Octahydro-1H-pyrrolo[3,4-b]pyridine (CAS RN 151213-40-0)	S
2933 99 80		1279891/2016	2,4-Dihydro-5-methoxy-4-methyl-3H-1,2,4-triazol-3-one (CAS RN 135302-13-5)	S
2934 99 90		1243015/2016	Thiophene-2-carbonyl chloride (CAS-RN 5271-67-0)	S
2935 00 90		1099844/2016	2-phenoxy methane sulphonamide (CAS RN 51765-51-6)	S

CN code	TARIC	Ref Mail	Description	S/Q
ex 2940 00 0 0	80	1289865/2016	D(+)-Trehalose dihydrate (CAS RN 6138-23-4)	S
2942 00 00		1242692/2016	Sodium triacetoxymethylborohydride	S
3204 12 00		1275088/2016	Colourant C.I. Acid Black 210 (CAS RN 85223-29-6 or 201792-73-6) and preparations based thereon with a colourant C.I. Acid Black 210 content of 50 % or more by weight	S
3204 12 00		1150396/2016	C.I. ACID BLACK 234 - 2,7-Naphthalenedisulfonic acid, 4-amino-3-[2-[4-[[[4-(2,4-diaminophenyl)diazenyl]phenyl]sulfonyl]amino]phenyl]diazenyl]-5-hydroxy-6-(2-phenyldiazenyl)-, sodium salt (1:2) — C.I. ACID BLACK 234	S
3204 12 00		1174638/2016	C.I. ACID BROWN 282 - Disodium [2,4-dihydro-4-[(2-hydroxy-5-nitrophenyl)azo]-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-)]-3-hydroxy-4-[(2-hydroxy-1-naphthyl)azo]-7-nitronaphthalene-1-sulphonato(3-)]chromate(2-)	S
3204 12 00		1179215/2016	C.I. ACID BROWN 432	S
3204 12 00		1174713/2016	C.I. ACID BROWN 425 - Trisodium bis[2-[[2,4-dihydroxy-3-[(2-methyl-4-sulphophenyl)azo]phenyl]azo]benzoato(3-)]chromate(3-)	S
3204 12 00		1174679/2016	C.I. ACID BROWN 355 - Chromate(3-), [3-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]-2-hydroxy-5-nitrobenzenesulfonato(3-)]-3-hydroxy-4-[(2-hydroxy-1-naphthalenyl)azo]-7-nitro-1-naphthalenesulfonato(3-)]-, sodium	S
3204 12 00		1174621/2016	C.I. ACID BROWN 165 - Iron, complexes with diazotized 2-amino-4,6-dinitrophenol coupled with diazotized 4-nitrobenzenamine and 4-[(2,4-dihydroxyphenyl)azo]-5-hydroxy-2,7-— naphthalenedisulfonic acid, sodium salts	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
3204 12 00		1174607/2016	C.I. ACID BROWN 75 - 2,7-naphthalenedisulfonic acid, 4-amino-5-hydroxy-, diazotized, coupled with diazotized 2-amino-4,6-dinitrophenol, diazotized 4-nitrobenzenamine and resorcinol, sodium salts	S
3204 12 00		1174590/2016	C.I. ACID BROWN 58 - Tetrasodium 5-[[[2,4-dihydroxy-5-[[4-[[4-nitro-2-sulphonatophenyl]amino]phenyl]azo]phenyl]azo]-4-hydroxy-3-[[4-[[4-nitro-2-sulphonatophenyl]amino]phenyl]azo]naphthalene-2,7-disulphonate	S
3204 12 00		1150528/2016	C.I. ACID BLUE 193 - Disodium hydrogen bis[3-hydroxy-4-[[2-hydroxy-1-naphthyl]azo]naphthalene-1-sulphonato(3-)]chromate(3-)	S
3204 12 00		1150455/2016	C.I. ACID BLACK 210 - Disodium 4-amino-6-[[4-(N-(4-((E)-(2,4-diaminophenyl)diazenyl)phenyl)sulfamoyl)phenyl]diazenyl]-5-hydroxy-3-(E)-(4-nitrophenyl)diazenyl]naphthalene-2,7-disulfonate	S
3204 12 00		1179308/2016	C.I. SULPHUR BLACK 1 - Phenol, 2,4-dinitro-, sulfurized	S
3204 14 00		1179262/2016	C.I. DIRECT BLACK 168 - Trisodium 4-amino-3-[[4-[[4-[[2-amino-4-hydroxyphenyl]azo]phenyl]amino]-3-sulphonatophenyl]azo]-5-hydroxy-6-(phenylazo)naphthalene-2,7-disulphonate	S
3204 17 00		1349389/2016	Colourant C.I. Pigment Yellow 1 (CAS RN 2512-29-0) and preparations based thereon with a Colourant C.I. Pigment Yellow 1 content of 80 % or more by weight and containing no more than 0.003 % arylamine	S
3204 17 00		1349075/2016	Colourant C.I. Pigment Red 146 (CAS RN 5280-68-2) and preparations based thereon with a Colourant C.I. Pigment Red 146 content of 80 % or more by weight and containing not more than 0.003 % of arylamine	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
3204 17 00		1338994/2016	Colourant C.I. Pigment Orange 16 (CAS RN 6505-28-8) and preparations based thereon with a Colourant C.I. Pigment Orange 16 content of 90 % or more by weight)	S
3204 17 00		1349155/2016	Colourant C.I. Pigment Yellow 180 (CAS RN 77904-81-0) and preparations based thereon with a Colourant C.I. Pigment Yellow 180 content of 80 % or more by weight)	S
3204 19 00		1339019/2016	Colourant C.I. Solvent Yellow 124 (CAS 34432-92-3) and preparations based thereon with a Colourant C.I. Solvent Yellow 124 content of 50 % or more by weight	S
3204 19 00		1345713/2016	Colourant C.I. Solvent Red 135 (CAS RN 20749-68-2) and preparations based thereon with a Colourant C.I. solvent red 135 content of 95 % or more by weight	S
3206 20 00		1345688/2016	Colourant C.I. Pigment Yellow 34 (CAS RN 1344-37-2) and preparations based thereon with a Colourant C.I. Pigment Yellow 34 content of 80 % or more by weight)	S
3206 20 00		1345748/2016	Colourant C.I. Pigment Red 104 (CAS RN 12656-85-8) and preparations based thereon with a Colourant C.I. Pigment Red 104 content of 80 % or more by weight)	S
3208 90 19		1243090/2016	Solution containing by weight: — 0.1 % or more but not more than 15 % of polysiloxane polymer with alkyl or aryl substituents with pendant alkoxygroups — 70 % or more organic solvent containing at least propyleneglycolether and/or propylene glycol methylether acetate and/or propyleneglycol propylether	S
3504 00 90		1280036/2016	Eiweißstoffe; OSTEOCALCIN	S
3507 90 90		1289924/2016	Enzyme: SALICYLATE R2 BULK mit einer Enzymkonzentration von 6.0-7.4U/ml und einem PH-Wert von 6.5-8.5	S

CN code	TARIC	Ref Mail	Description	S/Q
ex 3507 90 90	90	1279938/2016	Enzyme: ACETAMINOPHEN R1 BULK mit einer Enzymkonzentration von 6.6-7.4 U/mL, PH-Wert 7.9-8.1 und o-Cresol Konzentration 3.40-4.10 mM.	S
3806 90 00 3909 40 00		1243125/2016	Phenolic modified derivative of rosin resin, — containing by weight 50 % or more but not more than 75 % of rosin esters, — with an acid value of not more than 25, of a kind used in offset printing	S
3815 19 90		1336293/2016	Catalyst [in the form of] cylindrical pellets, consisting of: — chromium trioxide (CAS RN 1333-82-0), — dichromium trioxide (CAS RN 1308-38-9), on a support of aluminium oxide (CAS RN 1344-28-1)	S
3824 90 92		1367671/2016	Mixture containing two or three of the following acrylates; — urethane acrylates, — tripropylene glycol diacrylate, — ethoxylated bisphenol A acrylate and poly(ethyleneglycol) 400 diacrylate	S
3824 90 93		1249613/2016	Mixture containing by weight — 70 % or more, but not more than 90 % (S)-indoline-2-carboxylic acid (CAS RN 79815-20-6) and — 10 % or more, but not more than 30 % o-chlorocinnamic acid (CAS RN 3752-25-8)	S
3824 90 93		1336307/2016	Preparation, consisting of acesulfame potassium (CAS RN 55589-62-3) and potassium hydroxide (CAS RN 1310-58-3)	S
3824 90 96		1268378/2016	Mixture with a non-stoichiometric composition: — with a crystalline structure, — with a dominating participation of magnesia-alumina spinel and with admixtures of silicate phases and aluminates, at least 75 % by weight of which make fractions with a grain size of 1-3 mm and at most 25 % make fractions with a grain size of 0-1 mm	S

CN code	TARIC	Ref Mail	Description	S/Q
3824 90 96		1289935/2016	Aqueous solution of sodium periodate (CAS RN 7790-28-5) with a concentration of 3.55 - 3.95 mM, adjusted to pH 9.6 to 9.8	S
3901 20 90		1530718/2016	100 % Recycled polyethylene resin, produced from used milk bottles, with "natural" colour, smell free, in the form of pellets, with a specific gravity of 0.940 or more but not exceeding 0.965, for use in the manufacture bottles or cartridges for faxes, copiers and printers (1)	S
3901 90 90		1249670/2016	Mixture containing by weight — 80 % or more, but not more than 94 % chlorinated polyethylene (CAS RN 64754-90-1) and — 6 % or more, but not more than 20 % styrene-acrylic copolymer (CAS RN 27136-15-8)	S
3906 90 90		1274541/2016	Acrylic Emulsion Polymer containing hydroxyethylmethacrylate monomer	S
3906 90 90		1274598/2016	Acrylic Emulsion Polymer containing between 15-30 % by weight of the steareth-20 methacrylate monomer and a crosslinking agent	S
3906 90 90		1274638/2016	Acrylic Emulsion Polymer containing styrene monomer and Poly(ethylene glycol) methacrylate	S
3907 20 20		1349038/2016	Dodecanol initiated random copolymer containing by weight: — 48 % or more but not more than 52 % of propylene oxide and — 48 % or more but not more than 52 % of butylene oxide	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
3910 00 00		1295050/2016	Preparations containing by weight: — at least 53 % Methacryoxy propylglycerol terminated polydimethylsiloxane (662148-59-6) and — at least 14.5 % N,N – Dimethylacrylamide (2680-03-7)	S
3910 00 00		1295010/2016	Preparations containing by weight: — at least 23 % 2-hydroxy-3-[3-{1,3,3,3-tetramethyl-1-[(trimethylsilyl)oxy]disiloxanyl}propoxy]propyl-2-methyl-2-propenoate, and — at least 17 % Monomethacryloxypropopyl polydimethylsiloxane (146632-07-7)	S
3926 30 00		1297204/2016	Plastic logo of the automobile manufacturer with mounting brackets on the back side whether or not chromed for use in the manufacture of goods of Chapter 87 (1)	S
3926 90 92		1336370/2016	Silicon shell for breast implant	S
4010 31 00 4010 33 00 4010 39 00		1297172/2016	Vulcanized rubber endless transmission belt of trapezoidal cross-section with longitudinal V-ribbed pattern on the inner side for use in the manufacture of goods of Chapter 87 (1)	S
4411 12 90 4411 92 10		1336266/2016	Plywood with: — a width of 210 mm or more but not more than 320 mm, — a length of 297 mm or more but not more than 450 mm, — a thickness of 0,45 mm or more but not more than 0,8 mm, [of a kind used in the manufacture of products falling within subheading 4820 and 4911]	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
5903 20 90		1361540/2016	Plastic-laminated textile fabric used for the manufacture of the retractable roof of motor vehicles, with the following characteristics: — with two layers; — the component of each layer is polyester or ether urethane foam (polyurethane foam); — with a weight of 150 g/m2 or more but not more than 500 g/m2; — with a thickness of 1 mm or more, but not more than 5 mm	S
5906 99 90		1361569/2016	Woven and laminated rubberised textile fabric used for the manufacture of the retractable roof of motor vehicles, with the following characteristics: — with three layers; — the outer layers consist of acrylic fabric or polyester; — the middle layer consists of rubber; — with a weight of up to 1300 g/m2; — with a thickness not exceeding 4 mm	S
8108 90 30		1362566/2016	Titanium of high purity 99,999 % by weight (or 5N) or 99,995 % by weight (or 4N5), in the form of cylindrical forged billets, with — a diameter of 140mm or more but not more than 200 mm . — a weight of 5 kg or more but not more than 300 kg	S
8407 33 20 8407 33 80		1272671/2016	Single cylinder, four stroke internal combustion engine with a cylinder capacity of more than 325 cm3 but not more than 570 cm3, — with overall dimensions of not more than: 320 mm (length) x 381 mm (width) x 550 mm (height), — a power of more than 22kW but not more than 35kW, — equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
8407 33 80 8407 34 10 8407 34 91		1272702/2016	Dual cylinder, four stroke internal combustion engine with a cylinder capacity of more than 850 cm ³ but not more than 1200 cm ³ , — with overall dimensions of not more than: 350 mm (length) x 480 mm (width) x 560 mm (height), — a power of more than 44kW but not more than 130kW, — equipped with output shaft having an end diameter of 30 mm and a taper of 6 degrees (+/- 1 degree) or ended with a boss	S
8409 91 00		1302002/2016	Fuel injector with solenoid valve for optimized atomization in the engine combustion chamber for spark-ignition internal combustion piston engines for use in the manufacture of motor vehicles of Chapter 87 (1)	S
8414 90 00		1275119/2016	Assembly containing: — a cast iron bearing housing — radial- and axial bearings — compressor- and turbine wheel, mounted at the same gasturbine shaft — oil connections whether or not containing a provision for watercoolingof the kind used in turbocompressors	S
8424 89 00		1297221/2016	Mechanical passenger car headlights washer equipped with telescopic hose, high pressure nozzles and mounting clamps for use in the manufacture of goods of Chapter 87 (1)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
8501 31 00		1268149/2016	Brushless DC motor assembly comprised of: — electronic control with Hall based position sensor, — voltage input 9V or more but not more than 16V, — external diameter 70 mm or more but not more than 80 mm, — output power 450 W or more but not more than 500 W, — maximum torque 50 Nm or more but not more than 52 Nm, — maximum rotation speed 280 rpm or more but not more than 300 rpm. — coaxial male spline outputs of outer diameter 20 mm (+/- 1 mm), 17 teeth and minimum length of teeth 25 mm (+/- 1 mm), — with distance between root of splines 119 mm (+/- 1 mm).	S
8504 31 80		1249730/2016	Transformers [having a power handling capacity not exceeding 1 kVA] for use in the manufacture of electronic drivers, control devices and LED light sources for lighting industry (1)	S
8504 31 80		1264704/2016	Chokes with one or more windings, having an inductance of not more than 350 mH per winding, for use in the manufacture of electronic drivers, control devices and LED light sources for lighting industry (1)	S
8505 11 00		1301940/2016	Articles in the form of a triangle, square or rectangle whether or not in bent shape and with some of the corners rounded off, intended to become permanent magnets after magnetization, containing neodymium, iron and boron, with dimensions: — a length of 9 mm or more but not more than 105 mm, — a width of 5 mm or more but not more than 105 mm, — a height of 2 mm or more but not more than 55 mm.	S

CN code	TARIC	Ref Mail	Description	S/Q
8511 30 00		1302174/2016	Assembly comprising at least one ignition coil: — with a length of 50 mm or more, but not more than 200 mm, — with an operating temperature of - 40 °C or more, but not more than 140 °C, — with a voltage of 9 V or more, but not more than 16 V, — whether or not with connecting cable for use in the manufacture of motor vehicles of Chapter 87 (1)	S
8511 40 00		1297418/2016	Starter for spark-ignition and compression-ignition engines with a voltage of 12 V, for use in the manufacture of goods of Chapter 87 (1)	S
8511 50 00		1301965/2016	Alternator with: — an amperage of 110 A or more, but not more than 140 A at 5 000 rpm and temperature of 20 °C, — ventilation openings and mounting brackets for use in the manufacture of motor vehicles of Chapter 87 (1)	S
8511 80 00		1302069/2016	Glow-plug for diesel engines with: — operating temperature more than 800 °C, — voltage of 5 V or more, but not more than 12 V, — heating rod containing silicon nitride (Si3N4) and molybdenum disilicide (MoSi2), — metal housing for use in the manufacture of motor vehicles of Chapter 87 (1)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
8518 29 95		1297282/2016	(...) for installation into the dashboard or into the door of the automobile --- AT - Mar 2016 --- Speaker — with a diameter of 25 mm or more but not more than 80 mm, — with frequency range of 150 Hz - 20 kHz, — with power of 5W or more, but not more than 40W, — whether or not with electric cable with connector for installation into the dashboard of the automobile (1)	S
8518 90 00		1264734/2016	Insert — of steel — plated with an zinc-nickel-alloy — measuring 60,30 mm (+0,00 mm / - 0,40 mm) x 15,5 mm (+0,00 mm / - 0,40 mm) x 4,40 mm (± 0,05 mm) mm of a kind used in passive radiators of loudspeakers	S
8526 91 20		1362652/2016	Radionavigation system for motor vehicles in the form of an electronic device with a programmable memory, without a screen, which enables the following main functions: — GPS, — radio, — head-up display, — rear-view camera and — control of air conditioning system	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
8528 59 70		1362626/2016	Multifunctional multimedia apparatus equipped with a screen having a diagonal measurement of 16 cm or more but not more than 25 cm, of a kind used in motor vehicles, which enables the following main functions : — radio-broadcast receiver (FM/AM tuner and DAB tuner), — GPS, — radionavigation system, — sound reproducing device and — rear-view camera	S
ex 8536 41 1 0	90	1289887/2016	Photoelektrisches Relais (sog. Photovoltaik Relais) bestehend aus einer GaAlAs-Leuchtdiode, einem galvanisch getrennten Empfängerschaltkreis mit photovoltaischem Generator und einem Leistungs-MOSFET (als Ausgangsschalter) in einem Gehäuse mit Anschlüssen, für eine Spannung von 60 Volt oder weniger und für eine Stromstärke von 2 Ampere oder weniger	S
ex 8536 41 9 0	89	1289909/2016	Photoelektrisches Relais (sog. Photovoltaik Relais) aus einer GaAlAs-Leuchtdiode, einem galvanisch getrennten Empfängerschaltkreis mit einem oder zwei photovoltaischen Generator(en) und zwei Leistungs-MOSFETs (als Ausgangsschalter), in einem Gehäuse mit Anschlüssen, für eine Spannung von 60 Volt oder weniger und für eine Stromstärke von mehr als 2 Ampere	S
ex 8536 49 0 0	99	1289954/2016	Photoelektrisches Relais (sog. Photovoltaik Relais) bestehend aus zwei GaAlAs-Leuchtdioden, zwei galvanisch getrennten Empfängerschaltkreisen mit photovoltaischen Generator(en) und vier Leistungs-MOSFETs (als Ausgangsschalter), in einem Gehäuse mit Anschlüssen, für eine Spannung von mehr als 60 Volt	S

← **Bitimlendirilmiş Tablo**

CN code	TARIC	Ref Mail	Description	S/Q
8536 50 11		1297377/2016	Push-button switch for keyless start for a voltage of 12 V in a plastic housing, comprising at least: — printed circuit board, — LED diode, — connector, — brackets for mounting for use in the manufacture of goods of Chapter 87 (1)	S
8537 10 99		1290001/2016	Intelligentes Motor-Treiber-Modul zum elektrischen Schalten oder Steuern von elektronischen Motorantrieben für eine Spannung von weniger als 1000 Volt	S
8537 10 99 9031 80 34		1297336/2016	Radar sensor with control unit for autonomous emergency car braking system (1)	S
ex 8543 70 9 0	99	1289982/2016	Galliumnitrid (GaN) Hochfrequenzverstärker, bestehend aus einer oder mehreren integrierten Schaltungen, einem oder mehr Kondensator-Chips und optionalen integrierten passiven Bauelementen sog. IPD auf einem Träger in einem Gehäuse montiert	S
ex 8543 70 9 0	99	1290007/2016	Hochfrequenzverstärker, bestehend aus einer oder mehreren integrierten Schaltungen, Kondensator-Chips und integrierten passiven Bauelementen sog. IPD auf einem Träger in einem Gehäuse montiert	S
8544 30 00		1268178/2016	Wire harness: — with an operation voltage of 12V, — wrapped in tape and covered in plastic convoluted tubing, — with 16 or more strand, with all terminals to be tin plated or equipped with connectors, of a kind used in off-road vehicles (UTV – utility terrain vehicles and ATV – all terrain vehicles)	S

← **Bitimlendirilmiş Tablo**

CN code	TARIC	Ref Mail	Description	S/Q
8544 30 00		1297250/2016	Extension two-core cable of automobile electronic parking brake in rubber with at least one waterproof connector of a kind used in the manufacture of goods of Chapter 87	S
8708 30 91		1297453/2016	Brake unit assembly, whether or not equipped with an electronic parking brake, comprising at least: — piston, — brake pads, — gasket, — venting valve for use in the manufacture of goods of Chapter 87 (1)	S
8708 40 20 8708 40 50		1272648/2016	Single input, three output gear box in cast aluminium housing with overall dimensions of 381 mm (width) x 285 mm (height) x 680 mm (length), equipped with at least: — a magnetic clutch, — a rotary switch incorporated to indicate gear position, — an input shaft with a length of 76 mm (+/- 1 mm) and a diameter of 22 mm (+/- 1 mm), ended with 19 teeth spline of a length of 27 mm (+/- 1 mm) and a diameter of 27 mm (+/- 1 mm), with a blind M8 threaded hole of a minimum depth of 25 mm (+/- 1mm), — two output bushings located parallelly to input shaft, ended with 28 teeth spline with an inner diameter of 29 mm (+/- 1 mm), — an output shaft with a length of 184 mm (+/- 1 mm), ended with 33 teeth spline with an outer diameter of 24 mm (+/- 1 mm) and a length of 42 mm (+/- 1)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
8708 40 20 8708 40 50		1272781/2016	Single input, triple output gear box in cast aluminium housing with overall dimensions of not more than: 445 mm (width) x 380 mm (height) x 455 mm (length), equipped with at least: — a magnetic clutch, — a rotary switch incorporated to indicate gear position, — an input shaft with a diameter of 24 mm (+/- 1 mm) and a length of 144 mm (+/- 3 mm) — an output shaft with a diameter of 24 mm (+/- 1 mm) and a length of 75 mm (+/- 3 mm), ended with 22 teeth spline of a length of 43 mm (+/- 1 mm) and an outer diameter of 22 mm (+/- 1 mm), — two output bushings of 29 mm (+/- 1 mm) length with coaxial spline with 28 teeth, a spline length of 23 (+/- 1mm) and a spline inner diameter of 29 mm (+/- 1 mm)	S
8708 40 20 8708 40 50		1272811/2016	Gear box assembly with two inputs and three outputs in cast aluminium housing with overall dimensions of 325 mm (width) x 462 mm (height) x 464mm (length), equipped with at least: — one input shaft with outer diameter of 17mm (+/- 1 mm), a length of 40mm (+/- 1 mm), ended with 17 teeth spline, — one input shaft of more than 140 mm but not more than 150mm, with two outer diameters of 25 mm (+/-1 mm) and of 20mm (+/- 1 mm) and a blind M12 threaded hole of a length of 20 mm or more — one output shaft with a length of 39mm (+/- 2mm), an outer diameter of 25mm (+/- 1mm), ended with 22 teeth spline, — one output shaft with a length of 30mm (+/- 2mm), an outer diameter of 25mm (+/- 1mm), ended with 22 teeth spline, — one output shaft with a length of 52mm (+/- 1mm), an end diameter of 25mm (+/- 1mm), a taper of 3 degrees (+/- 1 degree)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
8708 93 10 8708 93 90		1268272/2016	Mechanically operated output clutch for use with a rubber drive belt in a CVT gearcase (Continuously Variable Transmission): — designed to be bolted onto a splined shaft of outer diameter 23 mm, — with overall diameter not more than 266 mm (+/- 1 mm), — comprised of 2 sheaves with tapered faces, — sheaves having taper of 13 degrees each, — having main compression spring used to resist displacement between sheaves, — comprised of cam or spring to maintain proper belt tension	S
8708 93 10 8708 93 90		1268238/2016	Mechanically operated centrifugal clutch for use with a rubber drive belt in a continuously variable transmission (CVT), equipped with: — elements that activate the clutch at given rotation and generate (in this way) centrifugal force — shaft ended with 5 degree taper — 3 weights — 1 compression spring	S
8708 99 10 8708 99 97		1268308/2016	Six-layer composite fuel tank assembly comprised of: — fuel inlet — pump flange assembly (PFA), — ventilation with rollover valve mounted near the top of the tank, — threaded holes for PFA assembly, — rollover valve mounted near the top of the tank, of a kind used for all-terrain and utility terrain vehicles	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
8708 99 10 8708 99 97		1272733/2016	Single input, dual output gearcase (transmission) in cast aluminum housing, with overall dimensions of 273 mm (width) x 131 mm (height) x 187 mm (length). Comprising at least: — two electro-magnetic one direction clutches, working in opposite sides, — an input shaft with outer diameter of 24 mm (+/- 1 mm), ended with 22 teeth spline, — a coaxial output bushing with inner diameter of 22 mm (+/- 1 mm), ended with 22 teeth spline	S
8714 10 90		1264754/2016	Damper tubes — of 7050-173 aluminium alloy — anodised on the inner surface — with a mean roughness (Ra) of the inner surface of not more than 0,4 and — a maximum roughness height (Rt) of the inner surface of not more than 4,0	S
9001 90 00		1349100/2016	Fibre Optic Plates: — uncoated and unpainted, — of a length of 30mm or more, but not more than 234,5mm, — of a width of 7mm or more, but not more than 28mm, and — of a height of 0.5mm or more, but not more than 3mm of a kind used in dental x-ray systems	S
9002 90 00		1453077/2016	Infrared optical unit formed — a silicon lens diameter $62 \pm 0,05$ mm — assembled on a machined aluminum alloy support of a kind used for thermal cameras	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
9002 90 00		1453564/2016	Infrared optical unit composed of — a germanium lens with a diameter of 19 mm (± 0.05 mm), — a monocrystalline calcium fluoride lens with a diameter of 18 mm (± 0.05 mm), — a germanium lens with a diameter of 20.6 mm (± 0.05 mm), assembled on a machined aluminum alloy support, of a kind used for thermal imaging cameras	S
9002 90 00		1452940/2016	Infrared optical unit composed of — a monocrystalline silicon lens with a diameter of 84 mm (± 0.1 mm) and — a monocrystalline germanium lens with a diameter of 62 mm (± 0.05 mm) assembled on a machined aluminum alloy support, of a kind used for thermal imaging cameras	S
9002 90 00		1453621/2016	Infrared optical unit composed of — a silicon lens with a diameter of 29 mm (± 0.05 mm) and — a monocrystalline calcium fluoride lens with a diameter of 26 mm (± 0.05 mm), assembled on a machined aluminum alloy support, of a kind used for thermal imaging cameras	S
9002 90 00		1453232/2016	Infrared optical unit composed of — germanium lens with a diameter of 11 mm (± 0.05 mm), — a monocrystalline calcium fluoride lens with a diameter of 14 mm (± 0.05 mm), — a silicon lens with a diameter of 17 mm (± 0.05 mm), assembled on a machined aluminum alloy support, of a kind used for thermal imaging cameras	S
9002 90 00		1453419/2016	Infrared optical unit composed of a silicon lens with a diameter of 26 mm (± 0.1 mm), mounted on a machined aluminum alloy support, of a kind used for thermal imaging cameras.	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
9032 89 00		1264795/2016	Gas panel for regulating and controlling of the gas flow rate, working with plasma technology, comprising — an electronic mass flow regulator, suitable for receiving and sending of analogue and digital signals — four pressure transducers, — two or more pressure valves, — electric interfaces and — several connectors for gas lines — suitable for in-situ plasma bonding processes or for multi frequency bond activating processes	S
ex 1511 90 1 9 ex 1511 90 9 1 ex 1513 11 1 0 ex 1513 19 3 0 ex 1513 21 1 0 ex 1513 29 3 0	20 20 20 20 20 20	1/1/1999	Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of: — industrial monocarboxylic fatty acids of subheading 3823 19 10, — methyl esters of fatty acids of heading 2915 or 2916, — fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products, — fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products, — stearic acid of subheading 3823 11 00, — goods of heading 3401, or — fatty acids with high purity of heading 2915 (1)	S
ex 2009 89 9 9	96	948/06	Coconut water — unfermented, — not containing added spirit or sugar, and — in immediate packing of a content of 20 litres or more NL proposal 14.03.2016 Coconut water — unfermented, — not containing added spirit or sugar, and — in immediate packing of a content of 50 litres or more (2)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
2401 20 70		3956896/2015	Tobacco, fully or partially stripped, Dark Air Cured, with a nicotine content of no less than 8 %. --- DK - Feb 2016 --- 20.1.16 DK proposal: Tobacco, fully or partially stripped, Dark Air Cured, with a nicotine content of no less than 8 % Tobacco, raw or unprocessed, not stripped, Dark air cured, ("TX – PA GROS Strips")	S
ex 2519 90 10	10	254871/2011	Fused magnesia with a purity by weight of 94 % or more --- PL - Mar 2016 --- Fused magnesia with a purity by weight of 97 % or more	S
2906 11 00		1225/2/1981	Menthol (CAS RN 1490-04-6)	S
ex 2918 30 00	60	726505/2014	4-Oxovaleric acid (CAS RN 123-76-2)	S
ex 2924 19 00	40	1704/4/2002	N-(1,1-Dimethyl-3-oxobutyl)acrylamide (CAS RN 2873-97-4)	S
2932 99 00		1318/2008	1,2,3-Trideoxy-4,6:5,7-bis-O-[(4-propylphenyl)methylene]-nonitol, (CAS RN 882073-43-0)	S
ex 2933 69 80	10	1111604/2015	1,3,5-Triazinane-2,4,6-trione-1,3,5-triazine-2,4,6-triamine(1:1) (CAS RN 37640-57-6)	S
ex 3102 50 00	10	287398/2012	Natural sodium nitrate	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 3204 15 0 0	10	423/3/1994	Colourant C.I. Vat Orange 7 (C.I.Pigment Orange 43) (CAS RN 4424-06-0) and preparations based thereon with a colourant C.I. Vat Orange 7 (C.I.Pigment Orange 43) content of 20 % or more by weight	S
ex 3204 17 0 0	13	3045147/2013	Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61-2) with a colourant C.I. Pigment Red content of 90 % or more by weight --- COM-TXD - Jan 2016 --- Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61-2)	S
ex 3204 17 0 0	27	647137/2014	Colourant C.I. Pigment Blue 15:4 (CAS RN 147-14-8) and preparations based thereon with a colourant C.I. Pigment Blue 15:4 content of 35 % or more by weight --- UK - Mar 2016 --- Colourant C.I. Pigment Blue 15:4 (CAS RN 147-14-8) and preparations based thereon, containing by weight 95 % or more of an organic dyestuff	S
ex 3215 90 0 0	30	1281/2008	Disposable cartridge ink, containing by weight: — 1 % or more, but not more than 10 % of amorphous silicon dioxide or — 3,8 % or more of dye C.I. Solvent Black 7 in organic solvents for use in the marking of integrated circuitsAT proposal 10.03.2016 Disposable cartridge ink, containing by weight: — 5 % or more, but not more than 10 % of amorphous silicon dioxide or — 3,8 % or more of dye C.I. Solvent Black 7 in organic solvents for use in the marking of integrated circuits (1)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 3506 91 0 0	50	1254126/2015	<p>Preparation containing by weight:</p> <p>— 15 % or more but not more than 60 % of styrene butadiene copolymers or styrene isoprene copolymers and</p> <p>— 10 % or more but not more than 30 % of pinene polymers or pentadiene copolymers</p> <p>Dissolved in :</p> <p>— Methyl ethyl ketone (CAS RN 78-93-3)</p> <p>— Heptane (CAS RN 142-82-5), and</p> <p>— Toluene (CAS RN 108-88-3) or light aliphatic solvent naphtha (CAS RN 64742-89-8)</p> <p>--- UK - Mar 2016 ---</p> <p>Preparation containing by weight:</p> <p>— 34,5 % or more but not more than 60 % of styrene butadiene styrene copolymers, and</p> <p>— rosin esters.</p> <p>Dissolved in:</p> <p>— Methyl ethyl ketone (CAS RN 78-93-3),</p> <p>— Heptane (CAS RN 142-82-5), and</p> <p>— Toluene (CAS RN 108-88-3) or light aliphatic solvent naphtha (CAS RN 64742-89-8)</p>	S
ex 3824 90 9 2	69	1102055/2015	<p>Preparation containing by weight:</p> <p>— 80 % or more but not more than 92 % of Bisphenol-A bis(diphenyl phosphate) (CAS RN 5945-33-5)</p> <p>— 7 % or more but not more than 20 % oligomers of Bisphenol-A bis(diphenyl phosphate) and</p> <p>— not more than 1 % triphenyl phosphate (CAS RN 115-86-6)</p> <p>--- UK - Mar 2016 ---</p> <p>Preparation containing by weight:</p> <p>— 80 % or more but not more than 92 % of Bisphenol-A bis(diphenyl phosphate) (CAS RN 5945-33-5)</p> <p>— 7 % or more but not more than 20 % oligomers of Bisphenol-A phenol phosphate and</p> <p>— not more than 1 % triphenyl phosphite (CAS RN 101-02-0)</p>	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 3824 90 9 2	84	435/7/1992	Preparation in the form of two separate liquids which after mixing reacts to a petroleum resin. Both components contain: — by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), — a synthetic rubber, — whether or not containing by weight 7 % or more of tricyclopentadiene. — Each separate components contains: — either an aluminium-alkyl compound, — or an organic complex of tungsten — or an organic complex of molybdenum --- NL - Dec 2015 --- Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and: — either an aluminium-alkyl compound, — or an organic complex of tungsten — or an organic complex of molybdenum	S
ex 3824 90 9 3 ex 3824 90 9 6	87 44	1001959/2015	Non halogenated Flame retardant containing by weight: — 50 % (+ 2 %) Polyamide 6 (CAS RN 25038-84-4), and — 50 % (+ 2 %) red Phosphorus (CAS RN 7723-14-0)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 3824 90 9 6	46	1093245/2015	<p>Manganese zinc ferrite granulate, containing by weight:</p> <ul style="list-style-type: none"> — 52 % or more but not more than 76 % of iron(III)oxide, — 13 % or more but not more than 42 % of manganese oxide, and — 2 % or more but not more than 22 % of zinc oxide <p>--- DE - mar 2016 ---</p> <p>Manganese zinc ferrite granulate, containing by weight:</p> <ul style="list-style-type: none"> — 52 % or more but not more than 56 % of iron(III)oxide, — 25 % or more but not more than 42 % of manganese(II) oxide and — 3,5 % or more but not more than 22 % of zinc oxide 	S
ex 3901 90 9 0	57	3981218/2015	<p>Octene linear low-density polyethylene (LLDPE) in the form of pellets used in the co-extrusion processing of films for flexible food packaging with:</p> <ul style="list-style-type: none"> — 10 % or more but not more than 20 % by weight of octene, — a melt flow ratio of 9,0 or more, but not more than 10,0 (using ASTM D1238 10.0/2.16), — a melt index (190°C/2.16 kg) of 0,4 g / 10 min but not more than 0,6 g / 10 min, — a density (ASTM D4703) of 0,909 g/cm³ or more, but not more than 0,913 g/cm³, — a gel area per 24,6 cm² of not more than 20 mm²; and — an anti-oxidant level not exceeding 240 ppm 	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 3908 90 0 0	45	1111669/2015	1,4-Benzenedicarboxylic acid polymer with 2-methyl-1,8-octanediamine and 1,9-nonanediamine (CAS RN 169284-22-4) BE 11.03.2016 1,4-Benzenedicarboxylic acid polymer with 2-methyl-1,8-octanediamine and 1,9-nonanediamine in powder form (CAS RN 169284-22-4)	S
ex 3911 90 1 9	10	1450/7/1995	Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene)	S
ex 3919 10 8 0 ex 3919 90 0 0	85 28	253870/2009 254166/2009 PROLONG 2015	Poly(vinyl chloride), poly(ethyleneterephthalate), polyethylene or any other polyolefin film: — of a total thickness of 65 µm or more, — coated on one side with an acrylic UV- sensitive adhesive and a liner AT proposal 10.03.2016 Poly(vinyl chloride) or polyethylene or any other polyolefin film: — of a thickness of 65 µm or more, — coated on one side with an acrylic UV- sensitive adhesive and a polyester liner	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 3919 90 0	54	1282/2008 PROLONG 2015	<p>Poly(vinyl chloride) film, whether or not covered on the top side with a metallized layer of polyurethane and an adhesive and whether or not covered on the bottom side with a layer of polymer, containing- an acrylic adhesive with an adhesive strength of 70 N/m or more which whether or not is reduced upon irradiation, - with a total thickness without release liner of 78 microns or more, and- a release liner, whether or not equipped with oblate spheres and on one side embossedNL proposal 14.03.2016</p> <p>Poly(vinyl chloride) film, whether or not covered on one side with a layer of polymer, with</p> <p>— an acrylic adhesive with an adhesive strength of 70 N/m or more whether or not reduced upon irradiation,</p> <p>— a total thickness without release liner of 78 microns or more, and</p> <p>— a release liner, whether or not equipped with oblate spheres and on one side embossed</p>	S
ex 3920 20 2 9	92	1154/2008	<p>Mono-axial oriented film, of a total thickness of not more than 75 µm, consisting of two or three layers, each layer containing a mixture of polypropylene and polyethylene, with a core layer whether or not containing titanium dioxide, having:</p> <p>— a tensile strength in the machine direction of 140 MPa or more but not more than 270 MPa and</p> <p>— a tensile strength in the transverse direction of 20 MPa or more but not more than 40 MPa as determined by test method ASTM D882/ISO 527-3</p>	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 3920 20 2 9	93	1176/2009 461/7/1999 PROLONG 2015	Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, having: — a thickness of 55 µm or more but not more than 97 µm, — a tensile modulus in the machine direction of 0,75 GPa or more but not more than 1,45 GPa, and — a tensile modulus in the transverse direction of 0,20 GPa or more but not more than 0,55 GPa	S
ex 3920 99 5 9	50	738/1/1993	Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not more than 0,14 mm, impermeable to water vapour	S
ex 3921 19 0 0	91	1305/9/1994	Microporous polypropylene film of a thickness of not more than 100 µm	S
ex 7009 10 0 0	10	1074119/2012	Electro-cromic auto-dimming glass mirror, without housing, for motor vehicle rear-view mirrors: — whether or not equipped with plastic backing plate, — whether or not equipped with a heating element, — whether or not equipped with Blind Spot Module (BSM) display --- HU - Mar 2016 --- Electro-cromic auto-dimming glass for motor vehicle mirrors: — whether or not equipped with plastic backing plate, — whether or not equipped with a heating element, — whether or not equipped with Blind Spot Module (BSM) display	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
7019 40 00		3863360/2015	Woven fabrics of rovings made of e-glass — with a weight of 24,5 g/m2 or more, but not more than 209 g/m2 — impregnated with a silane, — with a moisture content by weight of not more than 0,1 % — with less than 3 hollowfibres per 105 threads for use in the manufacture of prepreg sheets or rolls of a kind used for the production of printed circuits (1)	S
ex 7410 21 0 0	70	362769/2013	Plates, rolls or sheets: — with at least one layer of woven glass fibre, impregnated with a fire- retardant artificial or syrnthetic resin with a glass transition temperature (Tg) of more than 130 °C (according to IPC-TM-650, method 2.4.25), — coated on one or both sides with a copper film with a thickness of not more than 3,2 mm, for use in the manufacture of circuit boards AT proposal 10.03.2016 Plates, rolls or sheets: — with at least one layer of woven glass fibre, impregnated with a fire-retardant artificial or syrnthetic resin with a glass transition temperature (Tg) of more than 170 °C (according to IPC-TM-650, method 2.4.25), — coated on one or both sides with a copper film with a thickness of not more than 0,15 mm, for use in the manufacture of circuit boards (1)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
7606 12 92		1165126/2015	<p>Cold rolled sheets of aluminium alloy</p> <p>— of a thickness of 0,230 mm or more but not more than 0,280 mm,</p> <p>— of a width of 1578 mm or more but not more than 1737 mm,</p> <p>— a temper H19 (hardness class of the material)</p> <p>— Elongation A50 4,2-6,5 % (aver. 5,2 %)</p> <p>— YS: min. 275 MPa, max 290 MPa, aver. 284 MPa</p> <p>— UTS: min. 304 MPa, max 316 MPa, aver. 309 MPa</p> <p>— Split UTS-YS : 25 MPa</p> <p>— suitable for High Speed can drawings process, Cupping press jam: less than 2/million, B/M Tear Off rate: Less than 4/million,</p> <p>for use in the manufacture of beverage cans</p> <p>--- FI - Mar 2016 ---</p> <p>Cold-rolled aluminium alloy sheets conforming to EN standard AW-3104 H19 (...)</p> <p>--- UK - Dec 2015 ---</p> <p>Cold rolled sheets of aluminium alloy conforming to EN standard AW-3104 H19</p> <p>— of a thickness of 0,245 mm or more but not more than 0,280 mm,</p> <p>— of a width of 1589 mm or more but not more than 1736 mm,</p> <p>for use in the manufacture of beverage cans</p> <p>(1)</p>	S
ex 8108 90 3 0	40	982694/2011	<p>Wire of an titanium alloy</p> <p>AT proposal 10.03.2016</p> <p>Wire of an titanium alloy containing by weight:</p> <p>— 22 % (± 3 %) of vanadium and</p> <p>— 4 % (± 0,5 %) of aluminium</p>	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 8108 90 3 0	50	167191/2010 PROLONG 2016	Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 or 4967 --- FR - Mar 2016 --- Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928, 4965 and 4967	S
ex 8108 90 5 0	70	982750/2011	Strip of an titanium alloy --- AT - Mar 2016 --- Strip of an alloy of titanium, containing by weight: — 15 % (± 1 %) of vanadium — 3 % (± 0,5 %) of chromium — 3 % (± 0,5 %) of tin and — 3 % (± 0,5 %) of aluminium	S
ex 8108 90 9 0 ex 9003 90 0 0	20 10	982936/2011	Parts of spectacle frames and mountings, including temples, swaging parts and bolts of the kind used for spectacle frames and mountings, of an alloy of titanium --- AT - Mar 2016 --- Parts of spectacle frames and mountings, including bolts of the kind used for spectacle frames and mountings, of an alloy of titanium	S
ex 8421 29 0 0 ex 8479 82 0 0 ex 8479 89 9 7	20 10 75	1262038/2015	Equipment for use in the manufacture of biopharmaceutical products comprising any of the following whether or not with associated vessels or tanks: — Ultrafiltration-diafiltration unit; — Automated control, testing and monitoring equipment for Clean in Process (CIP) and Sterilise in Place (SIP) activities; — Process vessels and tanks (1)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 8479 89 9 7	60	527496/2014	<p>Bioreactor for biopharmaceutical cell culture — having interior surfaces of type 316L austenitic stainless steel — with a process capacity up to 15 000 litres, whether or not combined with a "clean-in-process" system and/or a dedicated paired media hold vessel --- IE - Mar(1) 2016 ---</p> <p>Bioreactor for biopharmaceutical cell culture (having interior surfaces of type 316L austenitic stainless steel) with a process capacity up to 15 000 litres, whether or not combined with a "clean-in-process" system --- IE - Mar(2) 2016 ---</p> <p>Bioreactor for biopharmaceutical cell culture (having interior surfaces of type 316L austenitic stainless steel) with a process capacity of 50 litres, 500 litres, 3 000 litres or 10 000 litres, whether or not combined with a "clean-in-process" system</p>	S
ex 8483 40 2 9	50	248671/2011	<p>Gear set of cycloid gear type with: — a rated torque of 50 Nm or more but not more than 9 000 Nm, — standard ratios of 1:50 or more but not more than 1:475, (...) --- SE - Feb 2016 ---</p> <p>Gear set of cycloid gear type with: — a rated torque of 50 Nm or more but not more than 7 000 Nm, — standard ratios of 1:50 or more but not more than 1:270, — lost motion of not more than one arc minute, — an efficiency of more than 80 %, of a kind used in robot arms</p>	S
ex 8504 40 9 0	20	778/1/1993	Direct current to direct current converter	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 8506 50 1 0	10	3869578/2015	<p>Lithium cylindrical primary cells with:</p> <ul style="list-style-type: none"> — a diameter of 14,0 mm or more but not more than 26,0 mm; — a length of 2,2 mm or more but not more than 51 mm; — a voltage of 1,5 V or more, but not more than 3,6 V; — a capacity of 0,15 Ah or more, but not more than 5,00 Ah <p>for use in the manufacture of telemetry and medical devices, electronic meters or remote controls</p> <p>--- AT - Mar 2016 ---</p> <p>Lithium cylindrical primary cells with:</p> <ul style="list-style-type: none"> — a diameter of 14,0 mm or more but not more than 26,0 mm; — a length of 25 mm or more but not more than 51 mm; — a voltage of 1,5 V or more, but not more than 3,6 V; — a capacity of 0,80 Ah or more, but not more than 5,00 Ah <p>for use in the manufacture of telemetry and medical devices, electronic meters or remote controls</p> <p>(1)</p>	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 8507 60 0 0	71	1095345/2012	<p>Lithium-ion rechargeable batteries, with:</p> <ul style="list-style-type: none"> — a length of 700 mm or more, but not more than 2 820 mm — a width of 935 mm or more, but not more than 1 660 mm — a height of 85 mm or more, but not more than 700 mm — a weight of 280 kg or more, but not more than 700 kg — a power of not more than 175 kWh <p>--- NL - Mar 2016 ---</p> <p>Lithium-ion rechargeable batteries, with:</p> <ul style="list-style-type: none"> — a length of 700 mm or more, but not more than 2 820 mm — a width of 935 mm or more, but not more than 1 660 mm — a height of 85 mm or more, but not more than 700 mm — a weight of 280 kg or more, but not more than 700 kg — a power of not more than 130 kWh 	S
ex 8544 20 0 0	20	1233197/2015	<p>Antenna connecting cable for the transmission of analogue radio (AM/FM) and GPS signals, containing:</p> <ul style="list-style-type: none"> — coaxial cable with two or more cores, — two or more connectors, — 5 or more plastic clips for attachment to the dashboard <p>of kind used in the manufacture of goods of Chapter 87</p> <p>--- SK - Mar 2016 ---</p> <p>Antenna connecting cable for the transmission of analogue radio (AM/FM) and GPS signals, containing:</p> <ul style="list-style-type: none"> — a two-core coaxial cable, — two or more connectors, — 5 or more plastic clips for attachment to the dashboard <p>of kind used in the manufacture of goods of Chapter 87</p>	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 8548 90 9 0 ex 9013 20 0 0	48 50	3117/10/2004	Optical unit, containing at least — a laser diode and a photodiode operating at a typical wavelength of 635 nm or more but not more than 815 nm — an optical lens — a "Recording Photodetector Integrated Circuit" (PDIC) — a focussing and tracking actuator --- COM-TXD(baeu) - Jan 2016 --- Optical unit, consisting at least of a laser diode and a photodiode operating at a typical wavelength of 635 nm or more but not more than 815 nm	S
ex 8708 30 9 1	10	634869/2010 PROLONG 2016	Drum type parking brake: — operating within the service brake disk, — with a diameter of 170 mm or more but not more than 195 mm, for use in the manufacture of motor vehicles --- SK - Mar 2016 --- Drum type parking brake: — operating within the service brake disk, — with a diameter of 170 mm or more but not more than 175 mm, for use in the manufacture of motor vehicles (1)	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 8714 10 9 0	10	1144388/2015	<p>Inner tubes, — of SAE1541 carbon steel — with a hard chromium layer of 20 µm (+15 µm/-5 µm) — having a wall thickness of 1,45 mm or more, but not more than 1,5 mm — having an elongation at break of 15 % — slotted of a kind used for the production of motorcycle fork rods, --- AT - Mar 2016 ---</p> <p>Inner tubes, — of SAE1541 carbon steel — with a hard chromium layer of 20 µm (+15 µm/-5 µm) — having a wall thickness of 1,45 mm or more, but not more than 1,5 mm — having an elongation at break of 15 % — slotted of a kind used for the production of motorcycle fork rods,</p>	S
ex 9001 50 4 1 ex 9001 50 4 9	30 30	825118/2014	<p>Round organic uncut corrective eyeglass lens blanks, finished on both sides: — of a diameter of 4,9 cm or more but not more than 8,2 cm, — of a height of 0,5 cm or more but not more than 1,8 cm, measured when the lens is laid on a flat surface from the horizontal plane to the lens front surface optical centre of a kind used to be processed in order to be adapted to a pair of glasses</p>	S

Biçimlendirilmiş Tablo

CN code	TARIC	Ref Mail	Description	S/Q
ex 9001 50 8 0	30	824923/2014	<p>Round organic uncut, semi-finished eyeglass lens blank, finished on one side, of a kind used for the manufacture of finished eyeglass lenses in order to be adapted to a pair of glasses --- DE - Mar 2016 ---</p> <p>Round organic uncut corrective eyeglass lens blanks, finished on one side: — of a diameter of 5,9 cm or more but not more than 8,5 cm — of a height of 1,2 cm or more but not more than 3,5 cm, measured when the lens is laid on a flat surface from the horizontal plane to the lens front surface optical centre of a kind used to be processed in order to be adapted to a pair of glasses</p>	S

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)

Biçimlendirilmiş Tablo