

**1 Ocak 2019 Tarihinde AB Üyeleri Veya Ülkemiz Tarafından Askıya Alınması/Tarife Kontenjanı Açılması Talep Edilen Eşya**

**Not: Tabloda yer alan ürünlere ilişkin talepler GTİP bazında değil yanlarındaki özel tanımlar bazında incelenmektedir. Bu yüzden firmalarımızın tam olarak bu özel tanımlara sahip ürünleri ithal ettiklerinden (eşbaşvuru için) /ürettiklerinden (itiraz için) emin olmaları durumunda başvurularını iletmeleri gerekmektedir.**

CN code	TARIC	Reference Mail	Description	S/Q	Partner Position Country	Partner Position
2712 90 39		1384144/2018	Slack wax (CAS RN 64742-61-6)	Q/100000 tonnes,	DE	Applicant
2905 49 00		1376923/2018	Xylitol – a five-carbon polyhydric alcohol (sugary) in the form of white crystal powder (CAS RN 87-99-0)	Q/13 000 tonnes,	PL	Applicant
2921 42 00		1384239/2018	4-Fluoro-N-(1-methylethyl)benzeneamine (CAS RN 70441-63-3)	Q/500 000 kilograms,	DE	Applicant
2923 20 00		1504093/2018	Lecithin (CAS RN 8002-43-5) from soy, for use in the manufacturing of feed applications	Q/120000tonnes, 01.01-31.12	NL	Applicant
2924 29 70		1437227/2018	2'-Methoxyacetoacetanilide (CAS RN 92-15-9)	Q/190tonnes, 01.01-31.12	CZ DE	Applicant Opposed
2932 20 90		1448970/2018	Epsilon-Caprolactone (CAS RN 502-44-3)	Q/400000kilogram s, 01.01-31.12	TR	Applicant
2934 30 90		1581329/2018	2-methoxy-phenotiazine	Q/20tonnes, 01.01-31.12	HU	Applicant
3921 90 55		1425212/2018	Prepreg sheets or rolls of at least one layer of glass fibre fabric impregnated with epoxy resin with flame retardant fillers and having a glass transition temperature (Tg) greater than 130 ° C (according to IPC-TM-650, method 2.4.25)	Q/1000000square meters, 01.01-31.12	DE AT	Applicant Opposed

8413 91 00		1452415/2018	Pump head for two cylinder high pressure pump made of forged steel, with: <ul style="list-style-type: none"> <li>- milled threaded fittings with a diameter of 10 to 36,8 mm and</li> <li>- drilled fuel channels with a diameter of 3,5 to 10 mm</li> </ul> of a kind used in diesel injection systems	<b>Q/65000pieces, 01.01-31.12</b>	SE	Applicant
8482 99 00		1518429/2018	Brass cages <ul style="list-style-type: none"> <li>- continuously or centrifugally cast,</li> <li>- turned,</li> <li>- containing by weight 35 % or more, but not more than 38 % of tin,</li> <li>- containing by weight 0,75 %, but not more than 1,25 % of lead,</li> <li>- containing by weight 1,0 % or more, but not more than 1,4 % of aluminium,</li> <li>- with a Brinell-hardness of 95 HBW or more, but not more than 133 HBW,</li> <li>- with a tensile strength of 415 Pa or more, and</li> <li>- with an elongation of 25 % or more</li> </ul> of a kind used for the manufacture of ball bearings	<b>Q/35000pieces,</b>	AT	Applicant
2309 90 00		4693681/2017	Soya bean protein concentrate containing by weight: <ul style="list-style-type: none"> <li>- 60 % (± 10 %) of crude protein,</li> <li>- 5 % (± 3 %) of crude fibre, and</li> <li>- 5 % (± 3 %) of crude ash</li> </ul> for use in the manufacture of products of food and drink industry (1)	<b>Q/15000tonnes, 01.07-31.12</b>	UK	Applicant
2914 19 90		4615801/2017	09.11.17 TR: Acetylacetone (CAS RN 123-54-6) with a purity of % 99,5 min. containing: <ul style="list-style-type: none"> <li>- not more than 0,1 % of acetic acid</li> <li>- not more than 0,10 % of water</li> <li>- not more than 15 of colour (ahpa)</li> <li>- with reflective index of 0,002 or more but not more than 1,450</li> <li>- with a density of 0.970 g/cm³ or more but not more than 0,975 g/cm³ at 20 °C</li> </ul> 6.11.17 COMM proposal: Pentane-2,4-dione for use in the manufacture of calcium acetylacetonat (CAS RN 123-54-6)	<b>Q/550tonnes, 01.07-31.12</b>	TR DE	Applicant Opposed

			UK proposal: Pentane-2,4-dione for the production of calcium acetylacetonat (CAS RN 123-54-6)			
			Acetylacetone for the production of calcium acetylacetonat (CAS RN 123-54-6) (1)			
2926 10 00		910/2006	Acrylonitrile (CAS RN 107-13-1)	<b>Q/125000tonnes, 01.01-31.12</b>	ES PT TR BE DE FR ES NL PT	Applicant Applicant Applicant Co-applicant Co-applicant Co-applicant Opposed Opposed Opposed
3804 00 00		4615750/2017	Aqueous solution of sodium lignosulphonate containing by mass 55 % or more of sodium lignosulphonate calculated on dry matter	<b>Q/900tonnes, 01.01-31.12</b>	TR	Applicant
ex 2916 39 90	28	3078972/2014	2,5-dimethylphenylacetyl chloride (CAS RN 55312-97-5)	<b>Q/400tonnes, 01.01-31.12</b>	DE	Applicant
ex 2921 41 00	10	816326/2014	Aniline with a purity by weight of 99 % or more (CAS RN 62-53-3)	<b>Q/150000tonnes, 01.01-31.12</b>	HU SK DE BE DE DE	Applicant Applicant Co-applicant Opposed Opposed Opposed
ex 3204 11 00	75	3102883/2014	Colourant C.I. Disperse Yellow 54 (CAS RN 7576-65-0) and preparations based thereon with a colourant C.I. Disperse Yellow 54 content of 99 % or more by weight	<b>Q/250000kilogram s, 01.01-31.12</b>	UK	Applicant
ex 3913 10 00	10	311124/2013	Sodium alginate, extracted from brown seaweed (CAS RN 9005-38-3)	<b>Q/10000tonnes, 01.01-31.12</b>	DK AT	Applicant Co-applicant
ex 5906 99 90	20	1361569/2016	Woven and laminated rubberised textile fabric with the following characteristics: - with three layers,	<b>Q/375000square meters, 01.01-</b>	HU AT	Applicant Opposed

			<ul style="list-style-type: none"> <li>- one outer layer consists of acrylic fabric,</li> <li>- the other outer layer consists of polyester fabric,</li> <li>- the middle layer consists of chlorobutyl rubber,</li> <li>- the middle layer has a weight of 452 g/m<sup>2</sup> or more but not more than 569 g/m<sup>2</sup>,</li> <li>- the textile fabric has a total weight of 952 g/m<sup>2</sup> or more but not more than 1159 g/m<sup>2</sup>,</li> <li>- the textile fabric has a total thickness of 0,8 mm or more but not more than 4 mm,</li> </ul> <p>used for the manufacture of the retractable roof of motor vehicles (1)</p>	<b>31.12</b>		
ex 7019 40 00 ex 7019 52 00	70 30	1290020/2016	<p>E-fibre glass fabrics:</p> <ul style="list-style-type: none"> <li>- having a weight of 20 g/m<sup>2</sup> or more, but not more than 214 g/m<sup>2</sup>,</li> <li>- impregnated with silane,</li> <li>- in rolls,</li> <li>- having a humidity content by weight of 0,13 % or less, and</li> <li>- having not more than 3 hollow fibres out of 100 000 fibres,</li> </ul> <p>for the exclusive use in the manufacture of prepreps and copper clad laminates (1)</p>	<b>Q/6000000meters, 01.01-31.12</b>	DE AT FR FR	Applicant Co-applicant Opposed Opposed
ex 7607 11 90	83	4613389/2017	<p>Aluminium and magnesium alloy strip or foil:</p> <ul style="list-style-type: none"> <li>- of an alloy conforming to standards 5182-H19 or 5052-H19,</li> <li>- in rolls with an outside diameter of not more than 1 350 mm ,</li> <li>- of a thickness (tolerance - 0,006 mm) of 0,15 mm, 0,16 mm, 0,18 mm or 0,20 mm,</li> <li>- a width (tolerance ± 0,3 mm) of 12,5 mm, 15,0 mm, 16,0 mm, 25,0 mm, 35,0 mm, 50,0 mm or 356 mm,</li> <li>- a camber tolerance of not more than 0,5 mm/750 mm,</li> <li>- a flatness measurement of I-unit ±5,</li> <li>- a tensile strength of more than (5182-H19) 365MPa or (5052-H19) 320MPa, and</li> <li>- an elongation at break of more than (5182-H19) 3 % or (5052-H19) 2,5 %</li> </ul> <p>for use in the manufacture of slats for blinds (1)</p>	<b>Q/300tonnes, 01.01-01.07</b>	SE DE	Applicant Opposed
ex 8414 90 00	70	5572918/2016	<p>FR proposal for amended description: Aluminium alloy compressor wheel with:</p> <ul style="list-style-type: none"> <li>- a diameter of 20 mm or more, but not more than 130 mm, and</li> <li>- a weight of 5 g or more, but not more than 800 g</li> </ul> <p>for use in the manufacture of turbochargers for motors vehicles combustion engines</p>	<b>Q/5900000pieces, 01.01-31.12</b>	FR DE	Applicant Opposed

ex 8526 91 20	20	1752/2002	Aluminium alloy compressor wheel with: <ul style="list-style-type: none"> <li>- a diameter of 20 mm or more, but not more than 130 mm, and</li> <li>- a weight of 5 g or more, but not more than 800 g</li> </ul> for use in the manufacture of combustion engines (1)	Q/3000000pieces, 01.01-31.12	FR AT	Applicant Co-applicant
ex 8714 91 10 ex 8714 91 10	21 31	1095094/2012	AT-request for amendment: Bicycle frame, constructed from carbon fibres and artificial resin, unpainted (raw), painted, lacquered and/or polished, for use in the manufacture of bicycles (including e-bikes)  Bicycle frame, constructed from carbon fibres and artificial resin, painted, lacquered and/or polished, for use in the manufacture of bicycles (1)		NL AT	Applicant Co-applicant

CN code	TARIC	Reference Mail	Description	S/Q	Partner Position Country	Partner Position
1006 40 00		1586081/2018	Broken rice as per standard specifications	S	DK	Applicant
1511 10 90		1586120/2018	Crude palm oil as per standard specifications	S	DK	Applicant
1511 90 19		1586181/2018	Palm stearin as per standard specifications	S	DK	Applicant

1511 90 99		1586224/2018	Refined palm oil as per standard specifications	S	DK	Applicant
2710 19 21		1325/2013	Jet fuel	S	EU	Applicant
2825 90 85		1485905/2018	Lithium nickel cobalt manganese oxide (NCM) in powder form with: - a BET surface area of 0,10 m <sup>2</sup> /g or more but not more than 1,14 m <sup>2</sup> /g, - a lithium hydroxide content of not more than 0,6 %, - a water content of not more than 0,1 %	S	HU	Applicant
2826 90 80		1431947/2018	Lithium difluorophosphate (CAS RN 24389-25-1)	S	UK	Applicant
2826 90 80		1431876/2018 964029/2011	Lithium hexafluorophosphate (1-) (CAS RN 21324-40-3)	S	DE	Applicant
2835 10 00		1181595/2018	Aluminium Phosphinate (CAS RN 7784-22-7)	S	IT	Applicant
2850 00 20		1449139/2018	Cubic Boron nitride (CAS RN 10043-11-5) [in form of crystal powder]	S	AT	Applicant
2903 78 00		1498079/2018	Octafluoro-1,4-diiodobutane (CAS RN 375-50-8)	S	FR	Applicant
2904 99 00		1503502/2018	2-Nitrobenzenesulfonyl Chloride (CAS RN 1694-92-4)	S	FR	Applicant
2909 30 38		1286699/2018	Reaction mass of 1,1'-(isopropylidene)bis[3,5-dibromo-4-(2,3-dibromo-2-methylpropoxy)benzene] and 1,3-dibromo-2-(2,3-dibromo-2-methylpropoxy)-5-{2-[3,5-dibromo-4-(2,3,3-tribromo-2-methylpropoxy)phenyl]propan-2-yl}benzene	S	IT	Applicant
2909 30 38		1205555/2018	4-Benzyloxybromobenzene (CAS RN 6793-92-6)	S	IT	Applicant

2914 19 90		1449168/2018	Bis(pentane-2,4-dionato-κO2,O4)zinc (CAS RN 14024-63-6)	S	AT	Applicant
2914 29 00		1181517/2018	2-Cyclohexen-1-One (CAS RN 609-08-5)	S	IT	Applicant
2914 29 00		1427748/2018	oestr-5(10)-ene-3,17-dione (CAS RN 3962-66-1)	S	DE	Applicant
2914 50 00		1286738/2018	2-Hydroxy-4-octyloxybenzophenone (CAS RN 1843-05-6)	S	IT	Applicant
2914 50 00		1376861/2018	5-Methoxy-4'-trifluoromethylvalerophenone (CAS RN 61718-80-7)	S	ES	Applicant
2914 79 00		1171241/2018	1-[4-(benzyloxy)phenyl]-2-bromopropan-1-one (CAS RN 35081-45-9)	S	IT	Applicant
2915 70 40		1613375/2018	Methyl palmitate (CAS RN 112-39-0)	S	NL	Applicant
2915 90 30		1613283/2018	Methyl laurate (CAS RN 111-82-0)	S	NL	Applicant
2915 90 70		1612989/2018	Methyl octanoate (CAS RN 111-11-5), methyl decanoate (CAS RN 110-42-9) or methyl myristate (CAS RN 124-10-7)	S	NL	Applicant
2915 90 70		1428182/2018 287208/2012	2,2-Dimethylbutyryl chloride (CAS RN 5856-77-9)	S	DE	Applicant
2916 20 00		1457960/2018	Cyclopropanecarbonyl chloride (CAS RN 4023-34-1)	S	UK	Applicant

2916 39 90	1581495/2018	2-(4-(cyclopropanecarbonyl)phenyl)-2-methylpropanoic acid cyclohexylamine salt (CAS RN 1690344-90-1)	S	UK	Applicant
2917 12 00	1431922/2018	Bis(3,4-epoxycyclohexylmethyl) adipate (CAS RN 3130-19-6)	S	UK	Applicant
2917 19 80	1181574/2018	Diethylmethylmalonate (CAS RN 609-08-5)	S	IT	Applicant
2919 10 00	1286811/2018	Benzene-1,3-diyl tetraphenyl bis(phosphate) (CAS RN 57583-54-7)	S	IT	Applicant
2920 90 10	1457746/2018	Fluoro ethylene carbonate (CAS RN 114435-02-8)	S	UK	Applicant
2920 90 10	1432061/2018	Ethyl methyl carbonate (CAS RN 623-53-0)	S	UK	Applicant
2920 90 10	1432015/2018	Diethyl carbonate (CAS RN 105-58-8) of a purity by weight of 99.99 % or more	S	UK	Applicant
2920 90 10	1431973/2018	Ethylene carbonate (CAS RN 96-49-1) of a purity by weight of 99 % or more	S	UK	Applicant
2920 90 70	1287007/2018	2-isopropoxy-4,4,5,5-tetramethyl-1,3,2-dioxaborolane (CAS RN 61676-62-8)	S	ES	Applicant
2920 90 70	1432107/2018	Vinylene carbonate (CAS RN 872-36-6)	S	UK	Applicant
2921 19 99	1522681/2018	Dimethyl(tetradecyl)amine	S	DK	Applicant



2922 19 00	1384285/2018	2-Methoxymethyl-p-phenylenediamine (CAS RN 337906-36-2)	S	DE	Applicant
2922 29 00	1384331/2018	4-Chloro-2,5-dimethoxyaniline (CAS RN 6358-64-1)	S	DE	Applicant
2922 39 00	1462606/2018	3-(N,N-Dimethylaminomethyl)-5-methyl-2-hexanone oxalate	S	IT	Applicant
2922 50 00	1485875/2018	3,4-Dimethyl-L-Methyldopa hydrochloride monohydrate	S	HU	Applicant
2924 19 00	1384647/2018	2,2,2-trifluoroacetamide (CAS RN 354-38-1)	S	DE	Applicant
2924 29 70	1286881/2018	3,3'-bis(3,5-di-tert-butyl-4-hydroxyphenyl)-N,N'-hexamethylenedipropionamide (CAS RN 23128-74-7)	S	IT	Applicant
2926 90 70	1226325/2018	4-Bromo-2-chlorobenzonitrile (CAS RN 154607-01-9)	S	IT	Applicant
2926 90 70	1497873/2018	Acetonitrile (CAS RN 75-05-8)	S	HU	Applicant
2926 90 70	1376661/2018	2-(4-amino-2-chloro-5-methylphenyl)-2-(4-chlorophenyl) acetonitrile (CAS RN 61437-85-2)	S	ES	Applicant
2928 00 90	1181494/2018	P-Chlorophenylhydrazine Hydrochloride (CAS RN 1073-70-7) synonymous of 4- Chlorophenylhydrazine Hydrochloride	S	IT	Applicant
2930 90 98	1384682/2018	4,4'-sulfonyldiphenol (CAS RN 80-09-1)	S	DE	Applicant

2930 90 98		123456/2018	Sodium Disubstituted Alaninamide Sulfonate	<b>S</b>	IT	Applicant
2931 90 00		1457877/2018	Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate (CAS RN 84434-11-7)	<b>S</b>	UK	Applicant
2931 90 00		1120/2009 1230/2008 1457701/2018	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide (CAS RN 75980-60-8)	<b>S</b>	UK DE DE	Applicant
2932 99 00		1453681/2018	3-hydroxy-2-methyl-4-pyrone (CAS RN 118-71-8)	<b>S</b>	NL	Applicant
2933 29 90		1460666/2018	2-(2-chlorophenyl)-1-[2-(2-chlorophenyl)-4,5-diphenyl-2H-imidazol-2-yl]-4,5-diphenyl-1H-imidazole (CAS RN 7189-82-4)	<b>S</b>	UK	Applicant
2933 39 99		1286961/2018	2-(4,6-Bis-(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6)	<b>S</b>	IT	Applicant
2933 39 99		1428219/2018 287387/2012	6-Chloro-3-nitropyridin-2-ylamine (CAS RN 27048-04-0)	<b>S</b>	DE	Applicant
2933 39 99		1225963/2018	2-Amino-4-Methylpyridine (CAS RN 695-34-1)	<b>S</b>	IT	Applicant
2933 49 10		1520675/2018	Roxadustat (INN) (CAS RN 808118-40-3)	<b>S</b>	SI	Applicant
2933 49 90		1462805/2018	6,7-Dimethoxy-3,4- dihydroisoquinoline hydrochloride	<b>S</b>	IT	Applicant
2933 59 95		1376797/2018	1-Methylpiperazine or <i>N</i> -Methylpiperazine (CAS RN 109-01-3)	<b>S</b>	ES	Applicant

2933 79 00		1205508/2018	Methyl(S)-Boc-5-Pyrrolidone-2-Carboxylate (CAS RN 108963-96-8)	S	IT	Applicant
2933 99 80		1226201/2019	Methyl 3,5-diamino-6-chloropyrazine-2-carboxylate (CAS RN 1458-01-1)	S	IT	Applicant
2934 99 90		1226466/2018	Alpha lipoic acid (CAS RN 62-46-4)	S	IT	Applicant
2934 99 90		1453634/2018	(2b,3a,5a,16b,17b)-2-(morpholin-4-yl)-16-(pyrrolidin-1-yl)androstane-3,17-diol 17-acetate (CAS RN 119302-24-8)	S	NL	Applicant
2934 99 90		1453576/2018	(2b,3a,5a,16b,17b)-2-(morpholin-4-yl)-16-(pyrrolidin-1-yl)androstane-3,17-diol (CAS RN 119302-20-4)	S	NL	Applicant
2934 99 90		1181505/2018	2-Bromo-5-Benzoyltiophene (CAS RN 31161-46-3)	S	IT	Applicant
2941 90 00		1382576/2018	Ascomycin (CAS RN 104987-12-4)	S	ES	Applicant
3902 90 90		1581989/2018 xxxx/xx/1990	Synthetic poly-alpha-olefin having a viscosity of at least $38 \times 10^{-6} \text{m}^2 \text{s}^{-1}$ (38 centistokes) at 100°C measured using the ASTM D 445 method	S	BE	Applicant
3204 17 00		1431431/2018	Colourant C.I. Pigment Red 81:2 (CAS RN 75627-12-2) and preparations based thereon with a colourant C.I. Pigment Red 81:2 content of 30 % or more by weight	S	UK	Applicant
3204 17 00		1431496/2018	Colourant C.I. Pigment Red 146 (CAS RN 5280-68-2) and preparations based thereon with a colourant C.I. Pigment Red 146 content of 80 % or more by weight	S	UK	Applicant
3501 90 90		1503438/2018	Sodium caseinate (CAS RN 9005-46-3) in the form of powder with a protein content of more than 88 % by weight and non edible	S	FR	Applicant
3811 29 00		1498127/2017	Additive consisting of more than 50 % by weight of Dialkyl tartrate (Butanedioic acid, 2,3-dihydroxy-, mixed C12-16-alkyl and C13-rich C11-14-isoalkyl diesters, (2R,3R)-rel-) for use in	S	FR	Applicant

			the manufacture of blends of additives for lubricating oils (1)			
3815 19 90		1431371/2018	Catalyst consisting of Tungstosilicic acid (CAS RN 12027-43-9) fixed on a support of silicon dioxide in the form of powder	S	UK	Applicant
3824 99 93		1427706/2018	Mixture of phytosterols (CAS RN 949109-75-5) in powder form, obtained from vegetables and vegetable based oils containing <ul style="list-style-type: none"> <li>- 40 % or more but not more than 88 % of sitosterols</li> <li>- 20 % or more but not more than 63 % of campesterols</li> <li>- 14 % or more but not more than 38 % of stigmasterols</li> <li>- not more than 13 % brassicasterols</li> <li>- not more than 5 % sitostanols</li> </ul>	S	DE	Applicant
3824 99 96		1460735/2018	Sulphanediylidibenzene-4,1-diyl) bis (diphenylsulphonium) bis (hexafluoroantimonate) in propylene carbonate (CAS RN 89452-37-9 and 108-32-7)	S	UK	Applicant
3824 99 96		1460609/2018	(4-[4-(diphenylsulphanylium)phenyl]sulphanyl} phenyl) diphenylsulphonium bishexafluorophosphate in propylene carbonate (CAS RN 74227-35-3 & 108-32-7)	S	UK	Applicant
3824 99 96		1449239/2018	Cubic Boron nitride (CAS RN 10043-11-5), nickel coated [in form of crystal powder]	S	AT	Applicant
3906 90 90		1520854/2018	Aqueous dispersion (with an ethanol content of more than 10 but not more than 15 weight percent) of polymer particles based on copolymer epoxymethacrylate with divinylbenzene that after polymerization reacted with a glycerol derivate	S	BE	Applicant
3907 20 11		1586049/2018	2,3-Bis(methylpolyoxyethylene-oxy)-1-[(3-maleimido-1-oxopropyl)amino]propyloxy propane and chemical extension products of same	S	DK	Applicant
3907 20 20		1457919/2018	Mixture containing by weight: <ul style="list-style-type: none"> <li>- 5 % or more but not more than 15 % of glycerol, propylene oxide, ethylene oxide polymer (CAS RN 9082-00-2), and</li> <li>- 85 % or more but not more than 95 % of Sucrose, propylene oxide, ethylene oxide polymer (CAS RN 26301-10-0)</li> </ul>	S	UK	Applicant

3907 20 99	1425060/2018	N-(methoxypoly (ethylene glycol) -N-(1-acetyl- (2-methoxypoly (ethylene glycol)) -glycine (CAS RN 600169-00-4) with a number average molecular weight (Mn) of 40.000 Da	S	DE	Applicant
3907 20 99	1425084/2018	Emapticap pegol (INN) (CAS RN 1390630-22-4) conjugated with 40kDa polyethylene glycol	S	DE	Applicant
3907 20 99	1425112/2018	Olaptesed pegol (INN) (CAS RN 1390628-22-4) conjugated with 40kDa polyethylene glycol	S	DE	Applicant
3907 99 80	1425441/2018	Copolymer of phthalic acid isomers, aliphatic acids and glycols modified with fatty acid	S	PL	Applicant
3912 31 00	1485885/2018	Sodium carboxymethyl cellulose in powder form with: <ul style="list-style-type: none"> <li>- a water content not more than 15 %,</li> <li>- a viscosity not more than 9 600 mPas,</li> <li>- a purity of 95 % or more</li> </ul>	S	HU	Applicant
3919 90 80	1458568/2018	Self-Adhesive Glass Tape: <ul style="list-style-type: none"> <li>- with a thickness of 150 µm or more,</li> <li>- a tensile strength of not more than 310 N/cm,</li> <li>- an operating temperature of - 73°C to + 260°C,</li> <li>- coated on one side with a pressure sensitive silicon adhesive</li> </ul>	S	UK	Applicant
3919 90 80	1518372/2018	AT(03.04.2018) Polyethylene or polycarbonate film <ul style="list-style-type: none"> <li>- [- not in rolls]</li> <li>- one side covered with a release liner and partly printed, whereby part of the printing either gives information about the meaning of LED's visible at the unprinted areas, or marks those points which must be touched to operate the furniture system,</li> <li>- the other side partly covered with an adhesive layer and covered with a release liner</li> <li>- with transparent (unprinted) areas</li> <li>- cut into ready to use forms</li> <li>- with dimensions of not more than 14 cm x 2,5 cm</li> </ul> of a kind used for the manufacture of push-button switches for mechatronic system adjustable furniture  Polyethylene or polycarbonate film	S	AT	Applicant

3920 20 80	1458625/2018	<ul style="list-style-type: none"> <li>- [- not in rolls]</li> <li>- one side partly printed and covered with a release liner</li> <li>- the other side partly covered with an adhesive layer and covered with a release liner</li> <li>- with transparent (unprinted) areas</li> <li>- cut into ready to use forms</li> <li>- with dimensions of not more than 14 cm x 2,5 cm</li> </ul> <p>of a kind used for the manufacture of push-button switches for mechatronic system adjustable furniture</p>	S	UK	Applicant
3920 61 00	1427660/2018	<p>Fluorinated ethylene propylene resin, with</p> <ul style="list-style-type: none"> <li>- a thickness of 0,010mm or more but not more than 0,80 mm,</li> <li>- a width of 1 219 mm or more but not more than 1 575 mm</li> <li>- an elongation at break of not more than 300 %,</li> <li>- an operating temperature range of - 254 °C or more, but not more than + 205 °C</li> </ul>	S	DE DE	Applicant Opposed
3921 90 55	1502477/2018	<p>Extruded thermoplastic foils or films of modified polycarbonate, in rolls,</p> <ul style="list-style-type: none"> <li>- colorless or colored with pigments or fluorescent dyes,</li> <li>- with matt surface texture on both sides,</li> <li>- whether or not with scattering particles between 0.5 and 5 microns particle size,</li> <li>- a thickness of more than 50 µm but not more than 175 µm,</li> <li>- a width of 800 mm but not more than 1285 mm and</li> <li>- a length of 915 m, but not more than 1829 m</li> </ul>	S	FR EU	Applicant Opposed
3926 90 97	1171480/2018	<p>Glass fiber impregnated with epoxy resin one of kind used in production of printed circuit boards with :</p> <ul style="list-style-type: none"> <li>- a length of 280 meters,</li> <li>- a width of 150 mm</li> </ul>	S	SK	Applicant
5311 00 90	1496119/2018	<p>Gasket of a holder made of polyethylene foam, of a kind used in the manufacture of exterior rear-view mirrors of motor vehicles</p>	S	TR	Applicant
7318 24 00	1518399/2018	<p>Sisal cloth in rolls with;</p> <ul style="list-style-type: none"> <li>- a length of 20 meters or more but not more than 30 meters and</li> <li>- a maximum width of 2,5 meters</li> </ul> <p>used for polishing Stainless Steel Kitchenware</p>	S	AT	Applicant

7410 21 00		1502532/2018	<ul style="list-style-type: none"> <li>- injection moulded,</li> <li>- with a rockwell hardness of 38 (<math>\pm 1</math>) or 53 (+2/-1),</li> <li>- measuring 9 mm x 5,5 mm x 6,5 mm or more, but not more than 35 mm x 17 mm x 8 mm</li> </ul> <p>of a kind used for restraint joints for tubes and pipes</p>	S	FR EU	Applicant Opposed
7604 21 00		1521490/2018	<p>Foils, rolls :</p> <ul style="list-style-type: none"> <li>- with a width of 150 mm,</li> <li>- with a length of 280 m,</li> <li>- composed with one layer of glass epoxy of 100 <math>\mu</math>m colaminated with refined copper foil on one or two sides of 35 <math>\mu</math>m with a tolerance of 10 %</li> </ul> <p>of a kind used for smartcard connector and electronic assembly</p>	S	CZ	Applicant
8113 00 20		984106/2011	<p>Hollow extruded profiles of aluminium alloy EN AW – 6063;</p> <ul style="list-style-type: none"> <li>- of square dimension with rounded corners;</li> <li>- of dimension of 47 x 47 mm or more, but not more than 144 x 144 mm;</li> <li>- of length 3 000 mm;</li> <li>- with longitudinal outer ribbing;</li> <li>- with axially symmetrical inner cylindrical bore in centre, with diameter of 32 mm or more, but not more than 125 mm;</li> <li>- with holes in the corners;</li> <li>- tolerance limits on H10</li> </ul>	S	AT	Applicant
8407 34 99		1178267/2018	<p>Cermet blocks containing by weight 60 % or more of aluminium and 5 % or more of boron carbide</p>	S	SK AT	Applicant Opposed
8409 91 00		1211033/2018	<p>Spark-ignition 4 cylinder internal combustion piston engine with multi-point injection (MPI) and a cylinder capacity of 1,999 cm<sup>3</sup>, a power of 112 kW and torque of 19,6 kgf.m for use in the manufacture of motor vehicles</p> <p>(1)</p>	S	SK AT	Applicant Opposed
		1211033/2018	<p>The engine block for spark-ignition 4 cylinder internal combustion piston engine of AlSi9Cu3 alloy with:</p> <ul style="list-style-type: none"> <li>- a material hardness of the cylinder liner area of HRC 18 or more, but not more than HRC 26,</li> <li>- a wall thickness of more than 3,0 mm, but not more than 5,5 mm,</li> <li>- a surface roughness in accordance with ISO 4287-1997</li> </ul> <p>for use in the manufacture of engines of motor vehicles</p> <p>(1)</p>	S	SK AT	Applicant Opposed

8409 99 00		1485985/2018	<p>Mechanical unit ensuring the movement of the camshaft with:</p> <ul style="list-style-type: none"> <li>- 8 oil chambers,</li> <li>- a phasing range of at least 38°, but not more than 62°,</li> <li>- a steel and/or steel alloy sprocket,</li> <li>- a steel and/or steel alloy rotor</li> </ul>	S	HU	Applicant
8409 99 00		1485961/2018	<p>Valve armature:</p> <ul style="list-style-type: none"> <li>- for the opening and closing of the flow of fuel,</li> <li>- consisting of a shaft and a blade,</li> <li>- with 8 holes on the blade,</li> <li>- made of metal and/or metal alloy(s)</li> </ul>	S	HU	Applicant
8415 90 00		1425543/2018	<p>Control case assemblies:</p> <ul style="list-style-type: none"> <li>- containing main PCB that is screwed inside a plastic cover, 5 pin terminal block connection, aluminum heat sink mounted on main PCB,</li> <li>- with a main PCB size of 280(±5)mm x 155(±5)mm,</li> </ul> <p>for internal use in the manufacture of air conditioners.</p>	S	TR	Applicant
8481 80 99		1485944/2018	<p>Pressure- and flow-control valve controlled by external electromagnet:</p> <ul style="list-style-type: none"> <li>- made of steel and/or steel alloy(s),</li> <li>- without integrated circuit,</li> <li>- of not more than 1000 kPa operating pressure,</li> <li>- with a flow quantity of not more than 5 l/min,</li> <li>- without an electromagnet</li> </ul>	S	HU	Applicant
8481 90 00		1485922/2018	<p>Magnetic rotation-sensor unit using Hall effect</p> <ul style="list-style-type: none"> <li>- with 2 or 4 integrated circuit,</li> <li>- for detecting the position of the air flow control valve in fuel-injection engines</li> </ul>	S	HU	Applicant
8483 50 80		1171356/2018	<p>Automotive battery sensor for current voltage, electrical current and temperature with:</p> <ul style="list-style-type: none"> <li>- voltage regulator and micro-controller,</li> <li>- LIN connection to the engine control unit,</li> <li>- ground cable</li> </ul> <p>for use in the manufacture of motor vehicles (1)</p>	S	SK	Applicant
8501 31 00		1449337/2018	<p>Permanently excited DC motor with</p> <ul style="list-style-type: none"> <li>- an external diameter of 35 mm or more but not more than 45 mm,</li> <li>- a rated speed of not more than 15 000 rpm,</li> <li>- a torque of 0,1 Nm or more, but not more than 0,8 Nm,</li> </ul>	S	AT	Applicant



8503 00 99	1521555/2018	<ul style="list-style-type: none"> <li>- an output of 50 W or more but not more than 200 W and</li> <li>- a supply voltage of 24 V or more but not more than 35 V</li> <li>- a speed and rotational direction encoder</li> <li>- with or without a speed or rotational direction sensor of resolver type or Hall effect type</li> </ul>	S	CZ	Applicant
8504 31 80	1425581/2018	<p>Rotor for an electric motor, with the rotor cylindrical body made of agglomerated ferrite and plastics and the shaft made of metal with the following dimensions:</p> <ul style="list-style-type: none"> <li>- diameter of the rotor body: 17 mm or more but not more than 37 mm;</li> <li>- length of the rotor body: 12 mm or more but not more than 36 mm;</li> <li>- shaft length: 52 mm or more but not more than 82 mm</li> </ul>	S	TR	Applicant
8504 31 80	1449556/2018	<p>Transformer reactors:</p> <ul style="list-style-type: none"> <li>- containing a core formed by steel alloy, a winding that produced from polyester imide-polyamide imide aluminium material and two terminal connectors with 0.250± %2 inches wide that produced from tinned brass material,</li> <li>- having of a rated current 11A AC and an inductance 6mH ± %10,</li> </ul> <p>for internal use in the manufacture of air conditioners.</p>	S	AT	Applicant
8504 31 80	1449501/2018	<p>Electrical Transformer with</p> <ul style="list-style-type: none"> <li>- a capacity of 433 VA</li> <li>- dimensions of not more than 37,3 x 38,2 x 28,5 mm</li> <li>- an operating temperature range of – 40 °C or more, but not more than + 125 °C</li> <li>- four inductively coupled copper wire windings and</li> <li>- 13 connection pins at the bottom</li> </ul> <p>[of a kind used for the manufacture of mechatronic systems for adjustable furniture]</p>	S	AT	Applicant
8504 31 80	1449456/2018	<p>Electrical Transformer with</p> <ul style="list-style-type: none"> <li>- a capacity of 432 VA</li> <li>- dimensions of not more than 24 mm x 21 mm x 19 mm</li> <li>- an operating temperature range of – 20 °C or more, but not more than + 85 °C</li> <li>- two windings and</li> <li>- 5 connection pins at the bottom</li> </ul> <p>[of a kind used for the manufacture of mechatronic systems for adjustable furniture]</p>	S	AT	Applicant
8504 31 80	1449456/2018	<p>Electrical Transformer with</p> <ul style="list-style-type: none"> <li>- a capacity of 216 VA</li> <li>- dimensions of not more than 27,1 x 26,6 x 18 mm</li> <li>- an operating temperature range of – 40 °C or more, but not more than + 125 °C</li> <li>- three inductively coupled copper wire windings and</li> <li>- 9 connection pins at the bottom</li> </ul>	S	AT	Applicant

8504 31 80		1449419/2018	<p>[of a kind used for the manufacture of mechatronic systems for adjustable furniture]</p> <p>Electrical Transformer with</p> <ul style="list-style-type: none"> <li>- a capacity of 192 VA</li> <li>- dimensions of not more than 27 x 26,5 x 18 mm</li> <li>- an operating temperature range of – 40 °C or more, but not more than + 125 °C</li> <li>- four inductively coupled copper wire windings and</li> <li>- 9 connection pins at the bottom</li> </ul> <p>[of a kind used for the manufacture of mechatronic systems for adjustable furniture]</p>	S	AT	Applicant
8504 31 80		1449377/2018	<p>Electrical Transformer with:</p> <ul style="list-style-type: none"> <li>- a capacity of 0,2 VA,</li> <li>- dimensions of not more than 15 x 15,5 x 14 mm,</li> <li>- an operating temperature range of – 10 °C or more, but not more than + 125 °C,</li> <li>- two inductively coupled copper wire windings,</li> <li>- 5 connection pins at the bottom, and</li> <li>- a copper shielding</li> </ul> <p>[of a kind used for the manufacture of mechatronic systems for adjustable furniture]</p>	S	AT	Applicant
8505 11 00		1431341/2018	<p>Permanent magnets of a neodymium alloy cylindrical shaped with notch and threading to the bore on one side, with:</p> <ul style="list-style-type: none"> <li>- a length of 97,5 mm or more, but not more than 225 mm;</li> <li>- a diameter of 19 mm or more, but not more than 25 mm</li> </ul> <p>for use in the manufacture of filtration devices for central heating systems</p>	S	UK	Applicant
8505 19 90		1502200/2018	<p>Barium or Strontium agglomerated ferrite article, in the shape of a half-sleeve or a quarter-sleeve, intended to become a permanent magnet after magnetization,</p> <ul style="list-style-type: none"> <li>- of a length of 30 mm or more but not more than 50 mm (± 1 mm),</li> <li>- of a width of 33 mm or more but not more than 55 mm (± 1 mm),</li> <li>- of a high of 12,5 mm or more but not more of 21,5 mm (± 1 mm)</li> <li>- of a thickness on the centre axis of 3,85 mm or more but not more than 6,8 mm (± 0,15mm),and</li> <li>- having an outer radius of 19 mm or more but not more than 29,4 mm (± 0,2mm)</li> </ul>	S	FR	Applicant
8507 60 00		1503782/2018	<p>Module of electrical battery made of 12 lithium-ion cells, with parallelepiped shape, with the following characteristics :</p> <ul style="list-style-type: none"> <li>- a length of 389 mm or more, but not more than 391 mm;</li> <li>- a width of 151 mm or more but not more than 153 mm;</li> <li>- a height of 108 mm or more but not more than 110 mm;</li> <li>- a mass of 13 kg or more but not more than 13,5 kg, and</li> </ul>	S	FR	Applicant

8529 90 92		1425412/2018	<ul style="list-style-type: none"> <li>- an energy of 2,6 kWh or more but not more than 2,9 kWh</li> </ul> <p>OLED modules, consisting of one or more TFT glass or plastic cells,</p> <ul style="list-style-type: none"> <li>- containing organic material,</li> <li>- not combined with touch screen facilities,</li> <li>- without inverters,</li> <li>- without backlight,</li> <li>- with one or more printed circuit boards with control electronics for pixel addressing only,</li> <li>- with or without back cover,</li> <li>- a diagonal measurement of the screen of 121 cm or more, but not more than 224 cm,</li> <li>- a thickness of the module not more than 55 mm,</li> <li>- with aspect ratio 16:9</li> </ul> <p>[of a kind used in the manufacture of TV sets only]</p>	S	PL	Applicant
8543 70 90		1178435/2018	<p>The Lane Departure Warning System (LDWS) with:</p> <ul style="list-style-type: none"> <li>- camera sensor,</li> <li>- control unit,</li> <li>- CAN bus</li> </ul> <p>for use in the manufacture of motor vehicles (1)</p>	S	SK	Applicant
8544 19 00		1382625/2018	<p>Wire consisting of an aluminum core and a concentric copper coating which is protected by a layer of varnish that can be polyester or polyurethane; and which has the following dimensions:</p> <ul style="list-style-type: none"> <li>- A volume percentage of copper of 10 % or more but not more than 15 %</li> <li>- A diameter, excluding the varnish, of 0.14mm or more but not more than 0.25mm</li> </ul> <p>for winding</p>	S	ES	Applicant
8544 42 90		1453445/2018	<p>PVC isolated flexible cable with:</p> <ul style="list-style-type: none"> <li>- a length of not more than 1800 mm</li> <li>- an operating voltage of 5V or more, but not more than 35V</li> <li>- a heat resistance of not more than 80°C</li> <li>- an over-moulded 8 pin MiniFit male connector on one end</li> <li>- either a 6 pin MiniFit socket or two over-moulded AMP connectors on the other end</li> <li>- a over-moulded resistor inside the connector and</li> <li>- a moulded strain relief on the cable</li> <li>- whether or not with a over-moulded dioce inside a connector</li> </ul> <p>[of a kind used for the manufacture of mechatronic systems for adjustable furniture]</p>	S	AT	Applicant
8544 42 90		1453405/2018	<p>PVC isolated flexible cable with:</p> <ul style="list-style-type: none"> <li>- two 3 pole connectors</li> </ul>	S	AT	Applicant

8544 42 90		1449665/2018	<ul style="list-style-type: none"> <li>- three or more wires AWG 18 and</li> <li>- a cable length of 2900 mm or more, but not more than 3100 mm</li> </ul> <p>[of a kind used for the manufacture of mechatronic systems for adjustable furniture]</p> <p>PVC isolated flexible six or eight wire cable with:</p> <ul style="list-style-type: none"> <li>- a length of not more than 1300 mm</li> <li>- an operating voltage of 5V or more, but not more than 35V</li> <li>- a heat resistance of not more than 80°C</li> <li>- either an over-moulded 8 pin MiniFit male connector or an over-moulded 6-pin DIN male connector on one end and</li> <li>- either an over-moulded 8 pin MiniFit socket or an 8 pin MicroFit male connector on the other end</li> </ul> <p>[of a kind used for the manufacture of mechatronic systems for adjustable furniture]</p>	S	AT	Applicant
8544 42 90		1449634/2018	<p>PVC isolated flexible eight wire cable with:</p> <ul style="list-style-type: none"> <li>- a length of not more than 2100 mm</li> <li>- an operating voltage of 5V or more, but not more than 33V</li> <li>- a temperature resistance of not more than 80°C</li> <li>- either an over-moulded 7 pin round 270° DIN male connector, a 6 pin A1101 male connector or a 8 pin A1001 male connector on one end and</li> <li>- at least two stripped and tinned wires on the other end</li> <li>- whether or not with mounted rubber pad with integrated strain relief</li> </ul> <p>[of a kind used for the manufacture of mechatronic systems for adjustable furniture]</p>	S	AT	Applicant
8544 42 90		1449608/2018	<p>PVC isolated flexible three wire cable with a cable length of 140 mm or more, but not more than 3100 mm:</p> <ul style="list-style-type: none"> <li>- either with two 3 pole connectors and a wire cross section of 0.75 mm<sup>2</sup></li> <li>- or with over-moulded connectors with locking shrouds, assembled rubber pads and integrated strain relief</li> </ul> <p>[of a kind used for the manufacture of mechatronic systems for adjustable furniture]</p>	S	AT	Applicant
8708 99 10		1171410/2018	Plastic air guide for directing air flow to the surface of intercooler	S	SK	Applicant
9032 89 00		1518341/2018	<p>Electronic Control Unit of battery supervision with a current sensor which has the following dimension with :</p> <ul style="list-style-type: none"> <li>- a length of 259 mm and more, but not more than 261 mm;</li> <li>- a width of 145 mm and more, but not more than 147 mm;</li> <li>- a height of 32mm and more, but not more than 35 mm</li> </ul>	S	FR	Applicant

9401 90 80		1584154/2018	<p>A set of plastic cushions with a tube system attached to a pad, consisting of:</p> <ul style="list-style-type: none"> <li>- two or more cushions made of plastic film;</li> <li>- two or more plastic tubes, whether or not equipped with caps or valves at the ends; and</li> <li>- pads made of felt, plastic or wire mats, or pads made of a combination of at least two of the materials;</li> </ul> <p>of the type used in producing car seats</p>	<b>S</b>	CZ EU	Applicant Opposed
ex 2933 39 99	46	5450881/2016	<p>DE(02.03.2018) Request for amendment: Fluopicolid (ISO) (CAS RN 239110-15-7)</p> <p>Current description: Fluopicolide (ISO) (CAS RN 239110-15-7) for use in the manufacture of pesticides (1)</p>	<b>S</b>	DE	Applicant
ex 2934 99 90	47	5450922/2016	<p>DE(02.03.2018): Request for amendment: Thidiazuron (ISO) (CAS RN 51707-55-2)</p> <p>Current Description : Thidiazuron (ISO) (CAS RN 51707-55-2) for use in the manufacture of pesticides (1)</p>	<b>S</b>	DE	Applicant
ex 3204 15 00	80	1528424/2017	<p>Colourant C.I. Vat Blue 1 (CAS RN 482-89-3) and preparations based thereon with a colourant C.I. Vat Blue 1 content of 94 % or more by weight</p>	<b>S</b>	TR DE	Applicant Opposed
ex 3204 17 00	24	384769/2013 5582640/2016 989554/2011	<p>UK (02.03.2018) Request for amendment: Colourant C.I. Pigment Red 57:1 (CAS RN 5281-04-9) and preparations based thereon with a Colourant C.I. Pigment Red 57:1 content of 20 % or more by weight</p> <p>Current description: Colourant C.I. Pigment Red 57:1 (CAS RN 5281-04-9) and preparations based thereon with a Colourant C.I. Pigment Red 57:1 content of 50 % or more by weight</p>	<b>S</b>	NL UK CZ DE DE	Applicant Applicant
ex 3801 90 00	20	1570492/2017	<p>HU(14.03.2018): Request for amendment Graphite based powder with:</p> <ul style="list-style-type: none"> <li>- an average particle size of 2,5 µm or more but not more than 26,5 µm,</li> <li>- an iron content of less than 40 ppm,</li> <li>- a copper content of less than 5 ppm,</li> <li>- a nickel content of less than 5 ppm,</li> </ul>	<b>S</b>	HU	Applicant

ex 3811 90 00	40	314105/2012	<ul style="list-style-type: none"> <li>- an average surface area (N<sub>2</sub> atmosphere) of 1,2 m<sup>2</sup>/g or more but not more than 20,4 m<sup>2</sup>/g, and</li> <li>- a magnetic metal impurity of less than 3 ppm</li> </ul> <p>Pitch coated graphite based powder with:</p> <ul style="list-style-type: none"> <li>- an average particle size of 10,8 µm or more but not more than 13,0 µm,</li> <li>- an iron content of less than 40 ppm,</li> <li>- a copper content of less than 5 ppm,</li> <li>- a nickel content of less than 5 ppm,</li> <li>- an average surface area (N<sub>2</sub>.atmosphere) of 3,0 m<sup>2</sup>/g or more but not more than 4,36 m<sup>2</sup>/g, and</li> <li>- a magnetic metal impurity of less than 0,3 ppm</li> </ul> <p>FR(09.03.2018) Solution of a quaternary ammonium salt based on polyisobutenyl succinimide, containing by weight 10 % or more but not more than 29,9 % of 2-ethylhexanol</p>	S	BE	Applicant
ex 3824 99 93	88	1164/07	<p>Solution of a quaternary ammonium salt based on polyisobutenyl succinimide, containing by weight 20 % or more but not more than 29,9 % of 2-ethylhexanol</p> <p>DE(02.03.2018) Request for amendment Mixture of phytosterols derived from wood and wood based oils (tall oil), containing by weight:</p> <ul style="list-style-type: none"> <li>- 60 % or more, but not more than 80 % of sitosterols,</li> <li>- not more than 15 % of campesterols,</li> <li>- not more than 5 % of stigmasterols,</li> <li>- not more than 15 % of betasitostanols</li> </ul> <p>Mixture of phytosterols derived from wood and wood based oils (tall oil), in the form of powder, containing by weight:</p> <ul style="list-style-type: none"> <li>- 60 % or more, but not more than 80 % of sitosterols,</li> <li>- not more than 15 % of campesterols,</li> <li>- not more than 5 % of stigmasterols and</li> <li>- not more than 15 % of betasitostanols</li> </ul>	S	FI	Applicant

ex 3826 00 10 ex 3826 00 10	30 39	343116/2013	<p>BE(13.03.2018)</p> <p>Mixture of fatty acid methyl esters containing by weight at least:</p> <ul style="list-style-type: none"> <li>- 50 % or more but not more than 58 % of C8-FAME</li> <li>- 35 % or more but not more than 50 % of C10-FAME</li> </ul> <p>for the manufacturing of high purity C8 or C10 fatty acid or fatty acid mixtures thereof or of high purity methylester of C8 or C10 fatty acid</p> <p>Mixture of fatty acid methyl esters containing by weight at least:</p> <ul style="list-style-type: none"> <li>- 50 % or more but not more than 58 % of C8-FAME</li> <li>- 35 % or more but not more than 50 % of C10-FAME</li> </ul> <p>for use in the manufacture of agricultural chemistry, (animal and human) food ingredients, additives to lubricant, solvents, lamp oil and firelighter components (1)</p>	S	BE	Applicant
ex 3901 10 10 ex 3901 90 80	20 50	3045217/2013 PROLONG 2016	<p>High flow linear low density polyethylene-1-butene / LLDPE (CAS RN 25087-34-7) in form of powder, with</p> <ul style="list-style-type: none"> <li>- a melt flow rate (MFR 190 °C/2,16 kg) of 16g/10min or more, but not more than 24 g/10 min and</li> <li>- a density (ASTM D 1505) of 0,922 g/cm<sup>3</sup> or more, but not more than 0,926 g/cm<sup>3</sup> and</li> <li>- a vicat softening temperature of min. 94 °C</li> </ul>	S	DE BG	Applicant Co-applicant
ex 3901 90 80	65	3009379/2013 PROLONG 2016	<p>Linear low-density polyethylene ( LLDPE) (CAS RN 9002-88-4) in the form of powder, with</p> <ul style="list-style-type: none"> <li>- more than 5 %, but not more than 8 % by weight of comonomer,</li> <li>- a melt flow rate of 15 g/10 min or more, but not more than 60 g/10 min and</li> <li>- a density of 0,922 g/cm<sup>3</sup> or more, but not more than 0,928 g/cm<sup>3</sup></li> </ul>	S	EL BG	Applicant Co-applicant
ex 3901 90 80	63	3891545/2015	<p>NL(06.02.2018):</p> <p>Octene linear low-density polyethylene (LLDPE) produced by a Ziegler-Natta catalyst method in the form of pellets with:</p> <ul style="list-style-type: none"> <li>- more than 10 % but not more than 20 % by weight of "comonomer" or "alpha-olefin",</li> <li>- a melt flow rate (MFR 190°C/2.16 kg) of 0.7 g / 10 min or more but not more than 0.9 g / 10 min, and</li> <li>- a density (ASTM D4703) of 0,911 g/cm<sup>3</sup> or more, but not more than 0,913 g/cm<sup>3</sup></li> </ul> <p>for use in the co-extrusion processing of films for flexible food packaging</p>	S	FI	Applicant

			<p>Octene linear low-density polyethylene (LLDPE) produced by a Ziegler-Natta catalyst method in the form of pellets with:</p> <ul style="list-style-type: none"> <li>- more than 10 % but not more than 20 % by weight of copolymer,</li> <li>- a melt flow rate (MFR 190°C/2.16 kg) of 0.7 g / 10 min or more but not more than 0.9 g / 10 min, and</li> <li>- a density (ASTM D4703) of 0,911 g/cm<sup>3</sup> or more, but not more than 0,913 g/cm<sup>3</sup></li> </ul> <p>for use in the co-extrusion processing of films for flexible food packaging (1)</p>			
ex 3901 90 80	80	631105/2010 PROLONG 2016	<p>Block copolymer of ethylene with octene in the form of pellets:</p> <ul style="list-style-type: none"> <li>- with a specific gravity of 0,862 or more, but not more than 0,865,</li> <li>- able to stretch to at least 200 % its original length,</li> <li>- with a hysteresis of 50 % (±10 %),</li> <li>- with permanent deformation of not more than 20 %,</li> </ul> <p>for use in the manufacture of napkin liners for babies (1)</p>	S	UK	Applicant
ex 3901 90 80	57	3981218/2015	<p>Octene linear low-density polyethylene (LLDPE) in the form of pellets of a kind used in the co-extrusion processing of films for flexible food packaging with:</p> <ul style="list-style-type: none"> <li>- 10 % or more but not more than 20 % by weight of octene,</li> <li>- a melt flow ratio of 9,0 or more, but not more than 10,0 (using ASTM D1238 10.0/2.16),</li> <li>- a melt index (190°C/2.16 kg) of 0,4 g / 10 min or more but not more than 0,6 g / 10 min,</li> <li>- a density of 0,909 g/cm<sup>3</sup> or more, but not more than 0,913 g/cm<sup>3</sup> using ASTM D4703,</li> <li>- a gel area per 24,6 cm<sup>3</sup> of not more than 20 mm<sup>2</sup>; and</li> <li>- an anti-oxidant level of not more than 240 ppm</li> </ul>	S	UK	Applicant
ex 3907 20 99	80	1652578/2017	Isoamyl alcohol polyoxyethylene ether (CAS RN 62601-60-9)	S	TR	Applicant
ex 3919 90 80 ex 9001 90 00	83 33	1159/2008	<p>Reflector or diffuser sheets, in rolls,</p> <ul style="list-style-type: none"> <li>- for protection against ultraviolet or infra-red heat radiation, to be affixed to windows or</li> <li>- for equal transmission and distribution of light, intended for LCD modules</li> </ul>	S	PL BE	Applicant Co-applicant
ex 3921 90 60 ex 5407 71 00 ex 5903 90 99	91 20 10	1247/6/1982	<p>NL(14.03.2018)Request for amendment:</p> <p>Ion-exchange membranes of fluorinated plastic material, for use in chlor-alkali electrolytic cells</p> <p>Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene</p>	S	UK	Applicant



			and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulphonic acid groups, whether or not in the potassium or sodium salt form			
ex 3926 30 00 ex 3926 90 97 ex 8708 29 10 ex 8708 29 90	10 23 10 10	1233437/2015	Plastic cover with clips for the exterior rear-view mirror of motor vehicles	S	SK	Applicant
ex 3926 90 97 ex 8538 90 99	37 40	848226/2014	SK: New proposal: Polycarbonate control interface buttons for steering pad switches coated on the outside with scratch resistant paint, in the packages of 500 pieces or more  Polycarbonate control interface buttons for steering pad switches coated on the outside with scratch resistant paint	S	SK	Applicant
ex 3926 90 97	77	5560026/2016	FR (13.03.2018) Request for amendment: Silicone decoupling ring with an inner diameter of 14,7 mm or more but no more than 16,0 mm of a kind used in car parking aid sensor systems  Current description: Silicone decoupling ring, with an inner diameter of 15,4 mm (+ 0,0 mm/- 0,1 mm), in immediate packings of 2 500 pieces or more, of a kind used in car parking aid sensor systems	S	FR	Applicant
ex 5603 14 90	50	4418530/2017	Non-woven fabric of microfibres, composed of polyester fibres with a uniform cross section with: - a weight of more than 150 g/m <sup>2</sup> , - a denier of 0,06 or more but not more than 0,50 den, - containing by weight 74 % or more of polyethylene terephthalate	S	IT DK	Applicant Co-applicant
ex 5903 10 90 ex 5903 20 90 ex 5903 90 99	10 10 20	698/7/1979	Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres	S	DE TR	Applicant Opposed
ex 7606 12 20	20	4639207/2017	Sign-plates composed of a polyethylene cellular core and outer layers of aluminium, with a total thickness of 1,8mm or more but not more than 4,2mm	S	UK EL ES ES	Applicant Opposed Opposed Opposed

ex 8409 91 00 ex 8409 99 00	50 55	371591/2013	<p>DE(02.03.2018) Request for amendment</p> <p>Exhaust manifold with turbine housing of turbochargers with:</p> <ul style="list-style-type: none"> <li>- a heat-resistance of not more than 1 050 °C, and</li> <li>- a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 181 mm"</li> </ul> <p>Exhaust manifold with turbine housing of turbochargers with:</p> <ul style="list-style-type: none"> <li>- a heat-resistance of not more than 1 050 °C, and</li> <li>- a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 130 mm</li> </ul>	S	EU FR  HU	Opposed Opposed  Applicant
ex 8411 99 00	30	371591/2013	<p>DE (02.03.2018) Request for amendment:</p> <p>Turbine housing of turbochargers with:</p> <ul style="list-style-type: none"> <li>- a heat-resistance of not more than 1 050 °C, and</li> <li>- a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 181 mm</li> </ul> <p>Turbine housing of turbochargers with:</p> <ul style="list-style-type: none"> <li>- a heat-resistance of not more than 1 050 °C, and</li> <li>- a hole to insert a turbine wheel, whereby the hole has a diameter of 28 mm or more, but not more than 130 mm</li> </ul>	S	HU	Applicant
ex 8482 10 10 ex 8482 10 90	40 30	847423/2014	<p>DE(02.03.2018): Request for amendment</p> <p>Ball bearings / ball bearing cartridges:</p> <ul style="list-style-type: none"> <li>- with an internal diameter of 3 mm or more,</li> <li>- with an external diameter of not more than 100 mm,</li> <li>- with a width of not more than 120 mm,</li> <li>- whether or not equipped with a duster,</li> </ul> <p>for use in the manufacture of belt drive steering systems of motor, electric power steering systems, steering gears or assy ball screw for steering gears or turbo compressors of the kind used in motor vehicles (electric turbocharger and exhaust gas turbocharger)</p> <p>Ball bearings:</p>	S	SK	Applicant

ex 8501 31 00 ex 8501 32 00	78 75	3812069/2015	<ul style="list-style-type: none"> <li>- with an internal diameter of 3 mm or more,</li> <li>- with an external diameter of not more than 100 mm,</li> <li>- with a width of not more than 40 mm,</li> <li>- whether or not equipped with a duster,</li> </ul> <p>for use in the manufacture of belt drive steering systems of motor, electric power steering systems or steering gears or assembly ball screw for steering gears (1)</p> <p>DE(02.03.2018) proposal for amended description: Automotive-ready, brushless and permanently excited direct current motor with:</p> <ul style="list-style-type: none"> <li>- a specified speed of not more than 4 100 rpm,</li> <li>- a minimum output of 400 W, but not more than 1,3 kW (at 12V),</li> <li>- a flange diameter of 90 mm or more, but not more than 150 mm,</li> <li>- a maximum length of 210 mm, measured from the beginning of the shaft to the outer ending,</li> <li>- a housing length of not more than 160 mm, measured from the flange to the outer ending,</li> <li>- a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 11 bore holes) aluminium diecast or sheet steel housing whether or not with a sealing compound (groove with an O-ring and grease),</li> <li>- a stator with single T-tooth design and single coil windings in 9/6 or 12/8 topology and</li> <li>- surface magnets</li> </ul> <p>Automotive-ready, brushless and permanently excited direct current motor with:</p> <ul style="list-style-type: none"> <li>- a specified speed of not more than 4 100 rpm,</li> <li>- a minimum output of 400 W, but not more than 1,3 kW (at 12V),</li> <li>- a flange diameter of 90 mm or more, but not more than 150 mm,</li> <li>- a maximum length of 200 mm, measured from the beginning of the shaft to the outer ending,</li> <li>- a housing length of not more than 160 mm, measured from the flange to the outer ending,</li> <li>- a maximum of two-piece (basic housing including electric components and flange with minimum 2 and maximum 6 bore holes) aluminium diecast housing whether or not with a sealing compound (groove with an O-ring and grease),</li> <li>- a stator with single T-tooth design and single coil windings in 12/8 topology, and</li> <li>- surface magnets</li> </ul>	S	DE	Applicant
ex 8501 31 00	40	229971/2009 PROLONG	<p>AT-request for amendment: Permanently excited DC motor with</p>	S	AT	Applicant

ex 8507 60 00	85	2015	<ul style="list-style-type: none"> <li>- a multiple-phase winding,</li> <li>- an external diameter of 30 mm or more but not more than 80 mm,</li> <li>- a rated speed of not more than 15 000 rpm,</li> <li>- an output of 45 W or more but not more than 300 W and</li> <li>- a supply voltage of 9 V or more but not more than 50 V</li> <li>- whether or not with a drive disc</li> <li>- whether or not with a crankcase</li> <li>- whether or not with a fan</li> <li>- whether or not with a cap assembly</li> </ul>	S	FR UK	Applicant Co-applicant
		165784/2010 PROLONG 2016	<p>Permanently excited DC motor with</p> <ul style="list-style-type: none"> <li>- a multiple-phase winding,</li> <li>- an external diameter of 30 mm or more but not more than 80 mm,</li> <li>- a rated speed of not more than 15 000 rpm,</li> <li>- an output of 45 W or more but not more than 300 W and</li> <li>- a supply voltage of 9 V or more but not more than 25 V</li> </ul> <p>UK Request for amended description:</p> <p>Lithium-ion Rectangular modules for incorporation in lithium-ion rechargeable batteries:</p> <ul style="list-style-type: none"> <li>- of a length of 300 mm or more, but not more than 350 mm</li> <li>- of a width of 79,8 mm or more, but not more than 225 mm</li> <li>- of a height of 35 mm or more, but not more than 168 mm</li> <li>- of a weight of 3,95 kg or more, but not more than 8,85 Kg</li> <li>- with a rating of 66,6 Ah or more, but not more than 129 Ah</li> </ul> <p>Rectangular modules for incorporation in lithium-ion rechargeable batteries:</p> <ul style="list-style-type: none"> <li>- of a length of 312 mm or more, but not more than 350 mm</li> <li>- of a width of 79,8 mm or more, but not more than 225 mm</li> <li>- of a height of 35 mm or more, but not more than 168 mm</li> <li>- of a weight of 3,95 kg or more, but not more than 8,56 kg</li> <li>- with a rating of 66,6 Ah or more, but not more than 129 Ah</li> </ul>			
ex 8507 60 00	47	1215681/2015	<p>TR(14.03.2018)</p> <p>Lithium-ion accumulators, with</p> <ul style="list-style-type: none"> <li>- a thickness of not more than 6 mm,</li> <li>- a width of not more than 100 mm,</li> <li>- a length of not more than 150,15 mm,</li> </ul>	S	TR	Applicant

			<ul style="list-style-type: none"> <li>- a nominal capacity of 1 000 mAh or more but not more than 10 000 mAh,</li> <li>- a weight of not more than 150 g</li> </ul> <p>for use in the manufacture of products falling within subheading 8517 12 00</p> <p>Lithium-ion accumulators, with</p> <ul style="list-style-type: none"> <li>- a thickness of not more than 4,15 mm,</li> <li>- a width of not more than 75,15 mm,</li> <li>- a length of not more than 150,15 mm,</li> <li>- a nominal capacity of 1 000 mAh or more but not more than 10 000 mAh,</li> <li>- a weight of not more than 150 g,</li> </ul> <p>for use in the manufacture of products falling within subheading 8517 12 00 (1)</p>			
ex 8714 91 10 ex 8714 91 10 ex 8714 91 10	23 33 70	3087055/2013	<p>AT- Request for amendment</p> <p>Frame, constructed from aluminium or aluminium and carbon fibres, for the use in the manufacture of bicycles (including e-bikes):</p> <p>Frame, constructed from aluminium or aluminium and carbon fibres, for the use in the manufacture of bicycles (1)</p>	S	NL AT	Applicant Co-applicant
ex 8714 99 10 ex 8714 99 10	20 89	4537684/2017	<p>AT-request for amendment:</p> <p>Bicycle handlebars,</p> <ul style="list-style-type: none"> <li>- with or without integrated stem,</li> <li>- either made out of carbon fibers and synthetic resin or made of aluminium,</li> </ul> <p>for use in the manufacture of bicycles</p> <p>Bicycle handlebars,</p> <ul style="list-style-type: none"> <li>- with or without integrated stem,</li> <li>- made out of carbon fibres and synthetic resin,</li> </ul> <p>for use in the manufacture of bicycles (1)</p>	S	DE AT	Applicant Co-applicant
ex 9002 11 00	85	3076474/2014	<p>DE request for amendment:</p> <p>Lens assembly with:</p> <ul style="list-style-type: none"> <li>- a horizontal field of view range of 50 deg or more, but not more than 200 deg,</li> <li>- a focal length of 1,16 mm or more, but not more than 5,45 mm,</li> </ul>	S	IE	Applicant

			<ul style="list-style-type: none"> <li>- a relative aperture of F/1,8 or more but not more than 2,6,</li> <li>- a diameter of 5 mm or more but not more than 18,5 mm,</li> </ul> for use in the manufacture of CMOS automotive cameras  Lens assembly with: <ul style="list-style-type: none"> <li>- a horizontal field of view range of 50 deg or more, but not more than 200 deg,</li> <li>- a focal length of 1,16 mm or more, but not more than 5,45 mm,</li> <li>- a relative aperture of F/2,0 or more but not more than F/2,6, and</li> <li>- a diameter of 5 mm or more but not more than 18,5 mm,</li> </ul> for use in the manufacture of CMOS automotive cameras (1)			
--	--	--	--	--	--	--

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1)