

## **CYCLE 2019-07**

List of new items – first version.

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests

The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic.

CN code	TARIC	Reference Mail	Description	S/Q	New or amendment request	Measure status	Partner Position Country	Partner Position	Public Comments
1516 20 10		4960995/2018	Hydrogenated Castor Oil	<b>Q/500tonnes,</b>	<b>New</b>	UNDER EXAMINATION	TR	Applicant	Round 7/2019 HCO is used in grease production.
2905 44 11		4884840/2018	D-glucitol in aqueous solution, containing 2 % or less by weight of D-mannitol, calculated on the D-glucitol content (CAS RN 50-70-4)	<b>Q/20000tonnes</b>	<b>New</b>	UNDER EXAMINATION	BE	Applicant	Round 7/2019 D-glucitol in aqueous solution, containing 2 % or less by weight of D-mannitol, calculated on the D-glucitol content

2910 30 00		4859202/2018	1-Chloro-2,3-epoxypropane (epichlorhydrin) (CAS RN 106-89-8)	<b>Q/21000000 kilograms,</b>	<b>New</b>	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Use as a monomer in the production of polymers. Raw material for further synthesis, e.g. epoxy resins, glycerine, paper additives, etc.
2916 14 00		5051698/2018	Methyl Methacrylate (CAS RN 80-62-6)	<b>Q/16000tonnes</b>	<b>New</b>	UNDER EXAMINATION	TR	Applicant	Round 7/2019 For polymerization in Polymer Emulsions
2917 11 00		4657972/2018	Diethyl oxalate (CAS RN 95-92-1)	<b>Q/250tonnes,</b>	<b>New</b>	UNDER EXAMINATION	IT	Applicant	Round 7/2019 Diethyl oxalate is a raw material used for the synthesis of other substances and chemical compounds.
2918 16 00		4990533/2018	Sodium gluconate (CAS RN 527-07-01)	<b>Q/1500tonnes,</b>	<b>New</b>	UNDER EXAMINATION	TR	Applicant	Round 7/2019 Concrete Additive
2921 19 99		4657923/2018	Octadecylamine (CAS RN 124-30-1)	<b>Q/200tonnes,</b>	<b>New</b>	UNDER EXAMINATION	IT	Applicant	ROUND 7/2019 Octadecylamine is a raw material used for the synthesis of other substances and chemical compounds.

2922 19 00		4990194/2018	Tipa 85 %, Triisopropanol amine 85 % (CAS RN 122-20-3)	<b>Q/150tonnes,</b>	<b>New</b>	UNDER EXAMINATION	TR	Applicant	Round 7/2019 Concrete additive
2922 19 00		4697079/2018	2-Benzylamoniethanol (CAS RN 104-63-2)	<b>Q/95tonnes,</b>	<b>New</b>	UNDER EXAMINATION	ES UK	Applicant Opposed	Round 7/2019 N-Benzylethanolamine (CAS 104-63-2) is used for the manufacture of 1.4.7.10 TETRABEZYL-1.4.7.10 TETRAAZACYCLODECANE (CAS 18084-64-5), intermediate of the product that can be used as a binder in chemistry
2923 20 00		1504093/2018	Lecithin (CAS RN 8002-43-5) [from soy], for use in the manufacture of feed applications	<b>Q/120000tonnes,</b>	<b>New</b>	UNDER EXAMINATION	NL	Applicant	Round 7/2019 Lecithin is used in the production of complementary animal feed
2930 90 98		4859271/2018	2-Chloro-4-(methylsulfonyl)-3-((2,2,2-trifluoroethoxy)methyl) benzoic acid (CAS RN 120100-77-8)	<b>Q/300000kilograms,</b>	<b>New</b>	UNDER EXAMINATION	DE	Applicant	Round 7/2019 End-use of imported product: Prepared herbicides
2930 90 98		4761430/2018	Bis[3-(triethoxysilyl)propyl]disulfide (CAS RN 56706-10-6)	<b>Q/3000tonnes,</b>	<b>New</b>	UNDER EXAMINATION	UK	Applicant	Round 7/2019 As a silane coupling agent in the manufacture

2933 99 80		4859238/2018	1,4,7,10-Tetraazacyclododecane (CAS RN 294-90-6)	<b>Q/40000kilograms</b>	<b>New</b>	UNDER EXAMINATION	DE	Applicant	of tyres for passenger cars  Round 7/2019 Raw material for end-use contrast media
3824 99 92		4842779/2018	Prepared binders for foundry moulds or cores; chemical products and preparations for the chemical or allied industries, incl. mixtures of natural products, n.e.s.- Liquid crystals	<b>Q/47kilograms,</b>	<b>New</b>	UNDER EXAMINATION	LV	Applicant	Round 7/2019 Prepared binders for foundry moulds or cores
3906 90 90		4961240/2018	Sodium Polyacrylate (CAS RN 9003-04-7)	<b>Q/20000tonnes</b>	<b>New</b>	UNDER EXAMINATION	TR	Applicant	Round 7/2019 Super Absorbent Polymer -
3907 20 20		4964098/2018	Polyether polyol obtained after tolüen diamine and propylene oxide reaction . OH 380-415 mg KOH/g ,Viscosity 15000-20000 mPas (CAS RN 63641-63-4)	<b>Q/400tonnes,</b>	<b>New</b>	UNDER EXAMINATION	TR	Applicant	Round 7/2019 Polyether polyol (CAS RN 63641-63-4)
3907 20 20		4964159/2018	Polyether polyol obtained after sucrose-glycerol and propylene oxide reaction .OH 430-470, Vis.15000-20000 mpas (CAS RN 9049-71-2)	<b>Q/3500tonnes,</b>	<b>New</b>	UNDER EXAMINATION	TR	Applicant	Round 7/2019 For use in appliance system production.
3908 10 00		4784542/2018	Polyamide-6,6 in a form of chips (CAS RN 32131-17-2)	<b>Q/6750tonnes,</b>	<b>New</b>	UNDER EXAMINATION	SK	Applicant	Round 7/2019 Polyamide-6,6 in a form of chips
7006 00 90		4842729/2018	Glass with indium tin oxide coating (clear sodalime glass, STN grade, one side ITO coating 80-100 ohms, another side 4 layers AR coating, 300x400x0.55mm)	<b>Q/86000pieces,</b>	<b>New</b>	UNDER EXAMINATION	LV	Applicant	Round 7/2019 Glass with indium tin oxide coating

ex 2924 19 00	85	385030/2013	3-Iodoprop-2-ynyl N-butylcarbamate (CAS RN 55406-53-6)	Q/350tonnes,	Amendment	UNDER EXAMINATION	NL	Applicant	Round 7/2019 Used to produce biocides
ex 7019 40 00 ex 7019 52 00	70 30	1290020/2016	E-fibre glass fabrics: - having a weight of 20 g/m <sup>2</sup> or more, but not more than 214 g/m <sup>2</sup> , - impregnated with silane, - in rolls, - having a humidity content by weight of 0,13 % or less, and - having not more than 3 hollow fibres out of 100 000 fibres, for the exclusive use in the manufacture of prepregs and copper clad laminates (1)	Q/3000000meters,	Amendment	UNDER EXAMINATION	DE & AT	Applicant	Round 7/2019 Re-opened to check how far the quality checks are advanced
8104 11 00		1/1/1994	Unwrought magnesium, containing at least 99,8 % by weight of magnesium	Q/120000tonnes,	Amendment	UNDER EXAMINATION	AT	Applicant	Round 7/2019 Request quota increase
8414 30 81		1097/2007	TR - request for amendment: Rotary type compressor, consisting of a single phase or three phase motor with a cooling capacity range between 2Kw to 8Kw, using a refrigerant fluid of type R32 or R410, for use in the manufacture of air conditioning machines (1)  Rotary type compressor, consisting of a single phase motor with a cooling capacity range between 2 Kw to 8 Kw, using a refrigerant fluid of type R 22 or R 410, for use in the manufacture of air conditioning machines (1)	Q/450000pieces	Amendment	UNDER EXAMINATION	TR	Applicant	Round 7/2019 Request for amendment in description

CN code	TARIC	Reference Mail	Description	S/Q	New or amendment request	Measure status	Partner Position Country	Partner Position	Public Comments
0402 21 18		3041752/2013 4705818/2018	Milk of camels of the species Camelus dromedaries, in powder form for use in the manufacture of dairy products and baby food as well as power drinks and chocolate	<b>S</b>	<b>New</b>	UNDER EXAMINATION	AT	Applicant	Round 7/2019 Re-submission The camel milk will in first line be used for the production of dairy products and baby food
0712 20 00		4884746/2018	Dehydrated and ground dried onion from white seed bred Californian varieties of Allium cepa with an allicin content of more than 5 000 mg/kg as determined by high performance liquid chromatography (HPLC) of a kind used in the manufacture of products in the food and drinks industry	<b>S</b>	<b>New</b>	UNDER EXAMINATION	BE	Applicant	Round 7/2019 Product is processed in the EU into custom seasoning blends
0712 90 90		4884791/2018	Dehydrated and ground garlic from white seed bred Californian varieties of Allium sativum with an allicin content of more than 10 000 mg/kg as determined by high performance liquid chromatography (HPLC) of a kind used in the manufacture of products in the food and drinks industry	<b>S</b>	<b>New</b>	UNDER EXAMINATION	BE	Applicant	Round 7/2019 Product is processed in the EU into custom seasoning blends.
1702 30 50		4861176/2018	Dehydrated corn syrup, containing by weight more than 99 % glucose (as determined by EU reg. 118/2010)	<b>S</b>	<b>New</b>	UNDER EXAMINATION	NL	Applicant	Round 7/2019 Intended to be used in the production of food preparations for infant use.
2815 12 00		4755854/2018	Aqueous solution of sodium hydroxide (CAS RN 1310-73-2) containing not less than 49 % but not greater than 51 % of	<b>S</b>	<b>New</b>	UNDER EXAMINATION	IE	Applicant	Round 7/2019 The commercial denomination is liquid

			sodium hydroxide						caustic soda supplied in aqueous solution
2818 10 11		4705865/2018	Sol-Gel corundum (CAS RN 1302-74-5) with an aluminium oxide content of 99,6 % or more by weight, [having a micro crystalline structure] [with an average particle size of 0,17 µm], in the form of rods with an aspect ratio of 1,3 or more, but not more than 6,0	S	New	UNDER EXAMINATION	AT	Applicant	Round 7/2019 It is a next-generation seeded gel product that offers the most extreme aspect ratio of any abrasive grain available
2828 10 00		4727358/2018	Calcium hypochlorite (CAS RN 7778-54-3) having an active chlorine content by weight of 65 % or more	S	New	UNDER EXAMINATION	AT	Applicant	Round 7/2019 Calcium hypochlorite
2903 78 00		4592963/2018	Heptafluoro-2-iodopropane (CAS RN 677-69-0)	S	New	UNDER EXAMINATION	ES	Applicant	Round 7/2019 Used as insecticide for the crops plagues control
2905 32 00		4755930/2018	(S)-(+)-1,2-Propanediol (CAS RN 4254-15-3)	S	New	UNDER EXAMINATION	IE	Applicant	Round 7/2019 Propanediol is used in the manufacture of bulk Active Pharmaceutical ingredients
2909 30 90		4592646/2018	1-Chloro-2-(4-ethoxybenzyl)-4-iodobenzene (CAS RN 1103738-29-9)	S	New	UNDER EXAMINATION	FR	Applicant	Round 7/2019 Chemical intermediate of active principle ingredient for the manufacture of pharmaceutical product
2910 90 00		4960627/2018	Phenyloxirane (CAS RN 96-09-3)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Intended use: Copolymerisation and formulation
2912 29 00		4854259/2018	Cyclohex-3-ene-1-carbaldehyde (CAS RN 100-50-5)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 An antioxidant (antiozonant) for

2912 49 00		4888586/2018	S-7-methoxycitronellal (CAS RN 3613-30-7)	S	New	UNDER EXAMINATION	HU	Applicant	vulcanisates such as tyres, seals, etc  ROUND 7/2019 S-methoxy citronellal is used as raw material in the manufacture of S-methoprene.
2915 90 70		4854304/2018	2,2-Dimethylbutanoyl chloride (CAS RN 5856-77-9)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Intended use of imported product: Prepared insecticides.
2916 39 99		4958109/2018	2-Phenylprop-2-enoic acid (CAS RN 492-38-6)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 raw material for synthesis / intermediate product
2918 30 00		4760470/2018	Ethyl acetoacetate titanate (CAS RN 83877-91-2)	S	New	UNDER EXAMINATION	UK	Applicant	Round 7/2019 Used commonly as an important additive in moisture curing room temperature vulcanizable (RTV) silicon sealant, catalyst for silane and silicone cross linking as well as moisture scavenger for sealant
2918 99 90		4727405/2018	Vanillic Acid (CAS RN 121-34-6) containing <ul style="list-style-type: none"> <li>- not more than 10 ppm of Palladium (CAS RN 7440-05-3),</li> <li>- not more than 10 ppm of bismuth (CAS RN 7440-69-9),</li> <li>- not more than 14 ppm of formaldehyde (CAS RN 50-00-0)</li> <li>- not more than 1,3 % by weight of 3,4-dihydroxybenzoic acid (CAS</li> </ul>	S	New	UNDER EXAMINATION	AT	Applicant	Round 7/2019 Raw material for the production of pharmaceutical product



2920 90 70		4650141/2018	RN 99-50-3) - not more than 0,5 % by weight of vanillin (CAS RN 121-33-5) and - not more than 0,2 % by weight of any other impurity  Diethyl phosphorochloridate (CAS RN 814-49-3)	S	New	UNDER EXAMINATION	IT	Applicant	Round 7/2019 The product is used in the synthesis for the production of Active Pharmaceutical Ingredient
2921 42 00		4648842/2018	5-Bromo-4-fluoro-2-methylaniline (CAS RN 627871-16-3)	S	New	UNDER EXAMINATION	IT	Applicant	Round 7/2019 The product is used for the production of the drug for the treatment of NASH non-alcoholic steatopathy.
2921 45 00		4886525/2018	(5 or 8)-Aminonaphthalene-2-sulphonic acid (CAS RN 51548-48-2)	S	New	UNDER EXAMINATION	CZ	Applicant	Round 7/2019 Basic raw material for production of pigments.
2921 45 00		4897351/2018	2-aminonaphthalene-1-sulfonic acid (CAS RN 81-16-3)	S	New	UNDER EXAMINATION	TR	Applicant	Round 7/2019 Raw material for textile dyestuff
2921 49 00		4650229/2018	2-Ethylaniline (CAS RN 578-54-1)	S	New	UNDER EXAMINATION	IT	Applicant	Round 7/2019 Raw material used for the synthesis of other substances and chemical compounds
2922 19 00		4592749/2018	3-Aminoadamantan-1-ol (CAS RN 702- 82-9)	S	New	UNDER EXAMINATION	IT	Applicant	Round 7/2019 Used in the synthesis of pharmaceutical intermediates and active pharmaceutical

2922 29 00		4650280/2018	o-Phenetidine (CAS RN 94-70-2)	S	New	UNDER EXAMINATION	IT	Applicant	ingredients Round 7/2019 O-Phenetidine is a raw material used for the synthesis of other substances and chemical compounds.
2923 90 00		4854327/2018	N,N,N-Trimethyl-tricyclo[3.3.1.1 <sup>3,7</sup> ]decan-1-aminium hydroxide (CAS RN 53075-09-5) in form of an aqueous solution with a content of N,N,N-trimethyl-tricyclo[3.3.1.1 <sup>3,7</sup> ]decan-1-aminium hydroxide by weight of 20 % or more but not more than 25 %	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Intended use: Production of synthetic chabazite zeolite
2924 19 00		4623600/2018	(S)-4-((tert-butoxycarbonyl)amino)-2-hydroxybutanoic acid (CAS RN 207305-60-0)	S	New	UNDER EXAMINATION	ES	Applicant	Round 7/2019 Product used in the manufacturing of a new Active Pharmaceutical Ingredient
2924 29 70		4886639/2018	N,N'-(2,5-Dichloro-1,4-phenylene)bis[3-oxobutyramide] (CAS RN 42487-09-2)	S	New	UNDER EXAMINATION	CZ	Applicant	Round 7/2019 Basic raw material for production of pigments
2924 29 70		4648603/2018	N-[(benzyloxy)carbonyl]glycyl-N-[(2S)-1-{4-[(tert-butoxycarbonyl)oxy]phenyl}-3-hydroxypropan-2-yl]-L-alaninamide	S	New	UNDER EXAMINATION	IT	Applicant	Round 7/2019 It is used as an intermediate utilized in a chemical synthesis for manufacturing a finished product available on the market.
2930 90 98		4658457/2018	Allyl isothiocyanate (CAS RN 57-06-7)	S	New	UNDER EXAMINATION	IT	Applicant	Round 7/2019 After the formulation of Allyl Isothiocyanate

2930 90 98		4990687/2018	Mercaptopropionic acid (BMPA) (CAS RN 107-96-0)	S	New	UNDER EXAMINATION	TR	Applicant	(active ingredient) with adjuvants, the new is able to gassify in the soil, carrying out the fumigation activity.
2932 19 00		4984249/2018	Dinotefuran (ISO) (CAS RN 165252-70-0)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Chain Transfer Agent
2932 19 00		4854367/2018	Tefuryltrione (ISO) (CAS RN 473278-76-1)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 It is used among other things as an active substance in veterinary drugs against ectoparasites.
2932 20 90		4753670/2018	3-Acetyl-6-methyl-2 H-pyran-2, 4(3 H )-dion (CAS RN 520-45-6)	S	New	UNDER EXAMINATION	AT	Applicant	Round 7/2019 The imported product is processed into a prepared suspension concentrate in a multistep process using solvents, emulsifiers and auxiliary agents. End-use of imported product: plant protection product, herbicide.
2932 99 00		4922553/2018	(2-Butyl-3-benzofuranyl)(4-hydroxy-3,5-diiodophenyl)methanone (CAS RN 1951-26-4)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Co-stabilizer for the processing of PVC, used in stabilizer systems for PVC, predominantly used in PVC window profile applications
									Round 7/2019 Raw material for synthesis / intermediate

2933 19 90		4623459/2018	4-Bromo-1-(1-ethoxyethyl)-1H-pyrazole (CAS RN 1024120-52-2)	S	New	UNDER EXAMINATION	FR	Applicant	product  Round 7/2019 Used as raw material which will go through a chemical transformation step in order to obtain a pharmaceutical intermediate to manufacture the final product (active pharmaceutical ingredient).
2933 39 99		4753711/2018	2,5-Dichloro-4,6-dimethylnicotinonitrile (CAS RN 91591-63-8)	S	New	UNDER EXAMINATION	AT	Applicant	Round 7/2019 Raw material for the production of an API
2933 39 99		4760424/2018	Chlorpyrifos-Methyl (CAS RN 5598-13-0)	S	New	UNDER EXAMINATION	UK	Applicant	Round 7/2019 Active ingredient used for the manufacture of several insecticide formulations
2933 39 99		4648901/2018	6-Bromopyridin-2-amine (CAS RN 19798-81-3)	S	New	UNDER EXAMINATION	IT	Applicant	Round 7/2019 The product is used as an intermediate to treat autoimmune diseases
2933 39 99		4620204/2018	Ethyl 2,6-dichloropyridine-3-carboxylate (CAS RN 58584-86-4)	S	New	UNDER EXAMINATION	ES	Applicant	Round 7/2019 Product used in the manufacturing of a new Active Pharmaceutical Ingredient
2933 39 99		4854440/2018	Methyl 1-(3-chloropyridin-2-yl)-3- hydroxymethyl-1H-pyrazole-5- carboxylate (CAS RN 960316-73-8)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Intended use of imported product: Plant protection products, prepared

2933 39 99		4854494/2018	Isomeric mixture of 1-(3-chloropyridin-2-yl)-3-[[5-(trifluoromethyl)-2H-tetrazol-2-yl]methyl]-1H-pyrazole-5-carboxylic acid (CAS RN 1352319-02-8) and 1-(3-chloropyridin-2-yl)-3-[[5-(trifluoromethyl)-1H-tetrazol-1-yl]methyl]-1H-pyrazole-5-carboxylic acid	<b>S</b>	<b>New</b>	UNDER EXAMINATION	DE	Applicant	insecticides  Round 7/2019 The imported product is synthesised as a raw material into a plant protection active substance in a multistep chemical process.
2933 54 00		4886604/2018	2,4,6(1H,3H,5H)-Pyrimidinetrione, 5,5'-(1,2-diazenediyl)bis- (CAS RN 25157-64-6)	<b>S</b>	<b>New</b>	UNDER EXAMINATION	CZ	Applicant	Round 7/2019 Basic raw material for production of pigments
2933 59 95		4593077/2018	1-(3-Chlorophenyl) piperazine (CAS RN 6640-24-0)	<b>S</b>	<b>New</b>	UNDER EXAMINATION	IT	Applicant	Round 7/2019 Intended use of the imported product: chemical synthesis
2933 69 80		4753738/2018	Troclosene sodium dihydrate (INN) (CAS RN 51580-86-0)	<b>S</b>	<b>New</b>	UNDER EXAMINATION	AT	Applicant	Round 7/2019 Troclosene sodium dehydrate is used as cleaning and disinfection agent.
2933 99 80		4884643/2018	Ipconazole (CAS RN 125225-28-7) with a purity by weight of 90 % or more	<b>S</b>	<b>New</b>	UNDER EXAMINATION	BE	Applicant	Round 7/2019 Fungicide active substance used in seed treatment
2933 99 80		4759965/2018	Hydrates of Hydroxybenzotriazole (CAS RN 80029-43-2 & CAS RN 123333-53-9)	<b>S</b>	<b>New</b>	UNDER EXAMINATION	IE	Applicant	Round 7/2019 The product is used in the manufacture of bulk Active Pharmaceutical ingredients and intermediates.

2933 99 80		4897580/2018	(1R,5S)-8-Benzyl-8-azabicyclo(3.2.1)octan-3-one hydrochloride (CAS RN 83393-23-1)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Intended use of imported product: Step preceding the synthesis of trospium chloride
2933 99 80		4697606/2018	L_Prolinamide (CAS RN 20232-39-7)	S	New	UNDER EXAMINATION	IT	Applicant	Round 7/2019 Used in the synthesis of pharmaceutical intermediates and active pharmaceutical ingredients
2934 99 90		4592679/2018	[(3aS,5R,6S,6aS)-6-Hydroxy-2,2-dimethyltetrahydrofuro[2,3-d][1,3]dioxol-5-yl] (morpholino)methanone (CAS RN 1103738-19-7)	S	New	UNDER EXAMINATION	FR	Applicant	Round 7/2019 Chemical intermediate of active principle ingredient for the manufacture of pharmaceutical product
2934 99 90		4697425/2018	Micafungin FR-179642 impurity (acid) or 5-((1S,2S)-2-((2R,6S,9S,11R,12R,14aS,15S,16S,20R,23S,25aR)-9-amino-20-((R)-3-amino-1-hydroxy-3-oxopropyl)-2,11,12,15-tetrahydroxy-6-((R)-1-hydroxyethyl)-16-methyl-5,8,14,19,22,25-hexaoxotetracosahydro-1H-dipyrrolo[2,1-c:2',1'-l][1,4,7,10,13,16]hexaazacyclohenicosin-23-yl)-1,2-dihydroxyethyl)-2-hydroxyphenyl hydrogen sulfate (CAS RN 168110-44-9)	S	New	UNDER EXAMINATION	ES	Applicant	Round 7/2019 Chemical compound intermediate used for the manufacture of an antifungal drug.
2934 99 90		4861238/2018	2-(dimethylamino)-2-[(4-methylphenyl)methyl]-1-[4-(morpholin-4-yl)phenyl]butan-1-one (CAS RN 119344-86-4)	S	New	UNDER EXAMINATION	NL	Applicant	Round 7/2019 It is a photo-initiator used in formulation for UV curing processes for specialty coatings and inks including indirect food-packaging

2935 90 90		4958187/2018	4-Chloro-3-pyridinesulphonamide (CAS RN 33263-43-3)	S	New	UNDER EXAMINATION	DE	Applicant	applications. Round 7/2019 Raw material for synthesis / intermediate product
2935 90 90		4593007/2018	1,3-Dimethyl-1H-pyrazole-4-sulfonamide (CAS RN 88398-53-2)	S	New	UNDER EXAMINATION	ES	Applicant	Round 7/2019 Product used in the manufacturing of a new Active Pharmaceutical Ingredient
2935 90 90		4958271/2018	4-[(3-Methylphenyl)amino]pyridine-3-sulfonamide (CAS RN72811-73-5)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Raw material for synthesis / intermediate product
3204 20 00		4861449/2018	Colourant C.I. Fluorescent Brightener 71 (CAS RN 16090-02-1) and preparations based thereon with a colourant C.I. Fluorescent Brightener 71 content of 60 % or more by weight	S	New	UNDER EXAMINATION	NL	Applicant	Round 7/2019 It is mainly used for the synthetic detergent such as washing powder, liquid detergent, softener, toilet soap and perfumed soaps etc.
3205 00 00		4838104/2018	D&C Red 34 Lake	S	New	UNDER EXAMINATION	IE	Applicant	Round 7/2019 D&C Red 34 Lake is a colouring agent used mainly in the Cosmetic industry for nail polish applications.
3205 00 00		4838121/2018	D&C Red 27 and D&C Red 28 aluminium lakes prepared from dyes	S	New	UNDER EXAMINATION	IE	Applicant	Round 7/2019 D&C Red 27 and D&C Red 28 Lake are colouring agents.
3815 12 00		4592717/2018	COM proposal for product description 10/9/2018:	S	New	UNDER	ES	Applicant	Round 7/2019 Used as a catalyst in the

			<p>Spherical catalytic converter with a diameter of 1,4 mm or more but not more than 2 mm composed of platinum on an aluminum oxide support, with a platinum content by weight of 0,2 % or more but not more than 0,5 %</p> <p>ES proposal for product description 3/9/2018: Spherical catalytic converter with a diameter equal to or greater than 1.4 mm and less than 2 mm composed of platinum on an aluminum oxide support, with a Platinum content between 0.2 and 0.5 % in weight</p>			EXAMINATION			dehydrogenation reaction from propane to obtain propylene
3815 12 00		4623658/2018	<p>Catalyst with monoliths of Nickel with a total weight between 1,26 %-1,29 %, and noble metals from 0,3 to 7 grams per liter, in aluminum oxide or cerium/zirconium oxide honeycomb structure with cell density from 400 to 900 cells per square inch, diameter ranging from 100 to 120mm and length ranging from 60 to 150mm, without housing, leads or similar. Catalyst used in automobile's production.</p>	S	New	UNDER EXAMINATION	ES	Applicant	Round 7/2019 Catalyst used in automobile's production.
3824 99 96		4834882/2018	<p>Buffer cartridge not exceeding 8000 ml containing:</p> <ul style="list-style-type: none"> <li>- 0.05 % or more but not more than 0.1 % by weight of 5-Chloro-2-methyl-2,3-dihydroisothiazol-3-one (CAS RN 55965-84-9), and</li> <li>- 0.05 % or more but not more than 0.1 % by weight of 2-Methyl-2,3-dihydroisothiazol-3-one (CAS RN 2682-20-4) as a biostatic</li> </ul>	S	New	UNDER EXAMINATION	UK	Applicant	Round 7/2019 It is used in the manufacture of a DNA sequencing kit



3904 69 80		4958337/2018	Polymers of vinyl chloride or of other halogenated olefins, in primary forms; fluoropolymers; others: copolymer of tetrafluoroethylene and ethylene, modified with a further monomer	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Plastics moulding material for processing by manufacturers in the EU into plastic mouldings, cable sheathing, plastic films, colour batches, pipes and divider sheets and architecture foils including industrial products and semi finished products. Used for example in the automotive and aviation industries, in the oil and gas sector and in architecture.
3904 69 80		4908926/2018	Polymers of vinyl chloride or of other halogenated olefins, in primary forms; fluoro-polymers; other: Ethylene tetrafluoroethylene-hexafluoropropylene copolymer (EFEP)	S	New	UNDER EXAMINATION	DE	Applicant	Round 7/2019 Plastic moulding material for further processing by manufacturing companies in the Community into plastic components, cable sheathing, plastic films, colour concentrates and similar industrial products and semi-finished products
3920 99 59		4753771/2018	Poly(tetrafluoroethylene) film with graphite embedded in the plastic, with a graphite content by weight of 10 % or more	S	New	UNDER EXAMINATION	AT	Applicant	Round 7/2019 for production of a yarn for braided packings.
3926 30 00		4891401/2018	Plastic internal door handle used in the manufacture of motor vehicles (1)	S	New	UNDER EXAMINATION	HU	Applicant	Round 7/2019 The product subject to this request is a mechanical door handle for opening the car's

5402 44 00		4780789/2018	<p>Synthetic elastomeric filament yarn:</p> <ul style="list-style-type: none"> <li>- untwisted or with a twist not exceeding 50 turns per metre, measuring 300 dtex or more but not more than 1000 dtex</li> <li>- composed of a segmented polyurethane urea containing a 3-methyl based glycol polymer</li> </ul> <p>for use in the manufacture of disposable hygiene products of heading 9619 (1)</p>	S	New	UNDER EXAMINATION	UK	Applicant	<p>door, it will be mounted in passenger cars in a car factory</p> <p>Round 7/2019 Used as a synthetic elastomer fibre in the manufacture of disposable hygiene products</p>
6909 19 00		4699502/2018	<p>Ceramic-carbon absorption cartridge:</p> <ul style="list-style-type: none"> <li>- extruded fired ceramic bound multicellular cylindrical structure</li> <li>- with a hardness of less than 6 on the Mohs scale</li> </ul> <p>containing:</p> <ul style="list-style-type: none"> <li>- 10 % by weight but not more than 30 % by weight of activated carbon</li> <li>- 70 % by weight but not more than 90 % by weight of ceramic binder</li> <li>- with a diameter of 29 mm or more but not more than 41mm</li> <li>- a length of not more than 150 mm</li> <li>- fired at temperature of 800°C or more</li> <li>- for vapors adsorption</li> </ul> <p>of a kind used for assembly in fuel vapors absorbers in fuel systems of motor vehicles</p>	S	New	UNDER EXAMINATION	PL	Applicant	<p>Round 2019-07 used as hydrocarbons adsorption supports in canisters</p>
7019 52 00		4884694/2018	<p>Epoxy resin coated glass cloth containing by weight:</p> <ul style="list-style-type: none"> <li>- 91 percent or more but not more than 93 percent glass fibers</li> <li>- 7 percent or more but not more than</li> </ul>	S	New	UNDER EXAMINATION	BE	Applicant	<p>Round 7/2019 For making epoxy/rubber based material for reinforcement and visco-elastic damper</p>

7607 20 90		4697798/2018	9 percent epoxy resin  Rolls of aluminium foil coated with polypropylene on one side and nylon on the other used to make pouches for Li ion battery cells	S	New	UNDER EXAMINATION	PL	Applicant	Round 7/2019 Aluminium foil used to make pouches for lit-ion battery cells.
8301 20 00		4765888/2018	Mechanical, whether or not electromechanical steering column lock: - in a metal housing, - whether or not with a holder for use in the manufacture of goods of Chapter 87 (1)	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 Steering column lock is mounted to the front module of a passenger car.
8407 34 10		4835468/2018	Engine, exclusively for use in the manufacture of the vehicles in heading 87, - spark ignition internal combustion, - has cylinder volume which is more than 2300 cm <sup>3</sup> , - produces more than 170 horsepower - provides more than 230 Nm torque, - operates together with electrical thermostat and two staged oil pump, - with low tensile piston ring, 3-piece air filter and metal spark plug (1)	S	New	UNDER EXAMINATION	TR AT	Applicant Opposed	Round 7/2019 For assembling and producing automobiles.
8409 91 00		4762376/2018	The air intake module for engine cylinders consisting of: - a suction pipe, - a pressure sensor, - an electric throttle, - hoses, - brackets for use in the manufacture of goods of Chapter 87 (1)	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 Air intake module for engine cylinders for mounting to the engine of a passenger car

8409 91 00		4835409/2018	Inlet manifold, exclusively for use in the manufacture of the motor vehicles; <ul style="list-style-type: none"> <li>- with wideness between 40mm to 70mm,</li> <li>- with valves which have 250mm to 350 mm length,</li> <li>- have air volume of 5.2 liters,</li> <li>- electrical flow control that provides maximum performance after 3200 d/d</li> </ul> (1)	S	New	UNDER EXAMINATION	TR	Applicant	Round 7/2019 Assembling and producing automobiles.
8409 99 00		4765326/2018	The exhaust gas recirculation assembly consisting of: <ul style="list-style-type: none"> <li>- a control unit,</li> <li>- an air throttle,</li> <li>- an intake pipe,</li> <li>- an outlet hose</li> </ul> for use in the manufacture of motors of motor vehicles (1)	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 Exhaust gas recirculation assembly mounted to the engine of a passenger car
8414 10 25		4762433/2018	Tandem pump consisting of an oil and vacuum pump with: <ul style="list-style-type: none"> <li>- oil pump displacement of 354 mm3 per revolution (<math>\pm 10</math> ml3),</li> <li>- vacuum pump displacement of 1 966 ml3 per revolution (<math>\pm 10</math> ml3),</li> <li>- oil pump working pressure 1.5 bar at 1 000 revolutions per minute,</li> <li>- vacuum pump performance – 666 mbar in 6 seconds at 750 revolutions per minute</li> </ul> for use in the manufacture of engines of motor vehicles (2)	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 Tandem pump consisting of an oil and vacuum pump for use in the manufacture of engines of motor vehicles
8414 10 89		4765822/2018	Electric vacuum pump with: <ul style="list-style-type: none"> <li>- CAN bus,</li> <li>- whether or not a rubber hose,</li> <li>- connecting cable with connector,</li> <li>- mounting bracket</li> </ul>	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 Electric vacuum pump is mounted to the front module of a passenger car.

8414 30 89		5050162/2018	for use in the manufacture of goods of Chapter 87 (2)  Car climate compressor with clutch assembly - scroll type	S	New	UNDER EXAMINATION	HU	Applicant	Round 7/2019 It is used for the manufacture of motor vehicles of heading 8703, it will be installed in passenger cars in a car factory.
8414 59 95		4700007/2018	Radial fan, with <ul style="list-style-type: none"> <li>- dimension of 85 X 25 mm,</li> <li>- weight of 120 g,</li> <li>- rated voltage of 13,6 VDC,</li> <li>- operating voltage of 9 VDC or more but not more than 16 VDC,</li> <li>- rated current of 1,1 A (TYP),</li> <li>- rated power of 15 W,</li> <li>- RPM operating range of 500 RPM or more but not more than 4800 RPM (free flow),</li> <li>- air flow of not more than 17,5 liter/s,</li> <li>- air pressure of not more than 16 mm H2O ≈ 157 Pa,</li> <li>- maximum overall sound pressure of 58 dB(A) at 4800 RPM,</li> <li>- operating ambient temperature non blowing of -40°C or more but not more than 85°C,</li> <li>- operating ambient temperature blowing of 0°C or more but not more than 85°C,</li> </ul> with FIN interface for communication with the heating and air-conditioning control unit used in car seat ventilation systems	S	New	UNDER EXAMINATION	PL	Applicant	Round 7/2019 Radial fans are used for the production of front and rear car seats. They are integrated into the seat-specific housing.

8414 80 11		4762339/2018	Single-stage turbocharger: - with a tightening torque of 0.5 kgfm or more but not more than 5.2 kgfm, - whether or not with a heat protector for use in the manufacture of engines of motor vehicles (1)	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 Single-stage turbocharger for mounting to the engine of a passenger car
8481 80 99		4887778/2018	4-way Reversing Valve - Refrigerant : R22 – R407C – R410A, - Maximum working pressure : 4,15 MPa, - Rated Voltage : AC24V/AC100V/AC220V/AC220-240V, rated : 50/60 Hz, - Minimum operative voltage : Not more than % 85 of rated voltage, - Refrigerant Temperature = between (-30°C) and (+120°C), and - Minimum Burst Pressure : 20,8 MPa	S	New	UNDER EXAMINATION	TR	Applicant	Round 7/2019 Valves are used to control the flow of air and liquid lines in split climates to be added the system.
8481 80 99		4887827/2018	Service Valve: - suits for R410A - the leakage ratio is less than 1.6g/a - the valve core must be functional after assembling - valve must be clear and the impurity must be less than 1.2 mg/PCS - airtight pressure of the valve body=4.2 MPa - withstanding pressure of the valve body=6.3 MPa	S	New	UNDER EXAMINATION	TR	Applicant	Round 7/2019 Valves are used to control the flow of air and liquid lines in split climates to be added the system
8484 20 00		4755348/2018	Mechanical sealing device with sliding rings made of carbon material and silicon carbide (liquid phase) with a thermal conductivity lower than 80W/mK and with	S	New	UNDER EXAMINATION	IT	Applicant	Round 7/2019 Mechanical sealing device to be used in manufacturing circulation

8501 10 10		4728772/2018	<p>a nitrile sealant on the external side to be used in manufacturing circulation pumps of cooling systems in motor vehicles</p> <p>Motors for air pumps, with:</p> <ul style="list-style-type: none"> <li>- operating voltage of 9 VDC or more but not more than 16 VDC</li> <li>- operating temperature range of - 40°C or more but not more than 80°C</li> <li>- an output not exceeding 18 W</li> </ul> <p>At no load:</p> <ul style="list-style-type: none"> <li>- speed of 4 763 RPM or more but not more than 4 869 RPM</li> <li>- rated current of not more than 0,2 A</li> </ul> <p>At load:</p> <ul style="list-style-type: none"> <li>- speed of 3 230 RPM or more but not more than 3 570 RPM</li> <li>- rated current of not more than 0,6 A</li> </ul> <p>used in pneumatic support systems for various types of car seats</p>	S	New	UNDER EXAMINATION	PL	Applicant	<p>pumps of cooling systems in motor vehicles</p> <p>Round 7/2019 The motors are used for the production of air pumps used in pneumatic support systems for various types of car seats.</p>
8507 60 00		4697852/2018	<p>Prismatic lithium-ion electric accumulators with:</p> <ul style="list-style-type: none"> <li>- a width of 173,0 mm (± 0,3 mm),</li> <li>- a thickness of 45.0 mm (± 0,3 mm),</li> <li>- a height 125,0 mm (± 0,3 mm),</li> <li>- a nominal voltage of 3.7 V, and</li> <li>- a nominal capacity of 94 Ah and/or 120 Ah</li> </ul>	S	New	UNDER EXAMINATION	PL	Applicant	<p>Round 7/2019 Sets cells are used for vehicles with electric motor as motors for propulsion, other than those capable of being charged by plugging to external source of electric power : scooters, cars and buses/coaches</p>
8507 60 00		4793865/2018	<p>Rectangular lithium-ion polymer accumulator also containing a battery management system capable of communicating via the vehicles internal CAN network with:</p> <ul style="list-style-type: none"> <li>- a total length of not more than 1600 mm,</li> <li>- a total width of not more than 448 mm,</li> </ul>	S	New	UNDER EXAMINATION	SE	Applicant	<p>Round 7/2019 The accumulator will be mounted into motor vehicle during manufacture in Plug-in Hybrid Electric (PHEV) battery system / Motor vehicle of heading 8703</p>

8507 90 30		4659305/2018	<ul style="list-style-type: none"> <li>- a total height of not more than 395 mm,</li> <li>- a total weight of 125 kg or more but not more than 135 kg,</li> <li>- a nominal voltage of 280 V or more but not more than 400 V,</li> <li>- a nominal capacity of 9,7 Ah or more but not more than 10,35 Ah,</li> <li>- a charging voltage of 110 V or more but not more than 230 V,</li> <li>- containing 6 modules with 90 cells or more but not more than 96 cells enclosed in a steel casing,</li> </ul> <p>to be placed in the transmission tunnel of a plug-in hybrid vehicle of heading 8703.</p>	S	New	UNDER EXAMINATION	PL	Applicant	<p>Round 7/2019</p> <p>The product is made of ceramic-coated PET film with specific crosslinking and porosity to allow the flow of lithium ions which are generated in electrochemical reactions in the Li ion battery.</p>
8507 90 80		4657656/2018	<p>Copper plate with:</p> <ul style="list-style-type: none"> <li>- a length of 36 mm or more but not more than 49 mm,</li> <li>- a width of 29,8 mm or more but not more than 45,2 mm, and</li> <li>- a thickness of 0,18 mm or more but not more than 0,66 mm</li> </ul> <p>used as the negative output, laser welded to the Li-Ion battery cell intended for electric cars, equipped with protective polypropylene tape with:</p> <ul style="list-style-type: none"> <li>- a length of 6,5 mm or more but not more than 16,5 mm, and</li> <li>- a width of 39 mm or more but not more than 56 mm,</li> </ul>	S	New	UNDER EXAMINATION	PL	Applicant	<p>Round 7/2019</p> <p>The copper plate (known as Lid) used as the negative output for manufacturing Li ion battery cells used in electric cars. The plate is provided with Lead Film i.e. a polypropylene layer to seal the AL. Pouch weld</p>



8507 90 80		4655767/2018	<p>the weld is sealed with aluminum foil enclosing battery</p> <p>Aluminum plate with:</p> <ul style="list-style-type: none"> <li>- a length of 36 mm or more but not more than 49 mm,</li> <li>- a width of 29,8 mm or more but not more than 45,2 mm, and</li> <li>- a thickness of 0,18 mm or more but not more than 0,66 mm</li> </ul> <p>used as the positive output, laser welded to the Li-Ion battery cell intended for electric cars, equipped with protective polypropylene tape with:</p> <ul style="list-style-type: none"> <li>- a length of 6,5 mm or more but not more than 16,5 mm, and</li> <li>- a width of 39 mm or more but not more than 56 mm</li> </ul> <p>the weld is sealed with aluminum foil enclosing battery</p>	S	New	UNDER EXAMINATION	PL	Applicant	<p>Round 7/2019</p> <p>The aluminium plate (known as Lid) used as the positive output for manufacturing Li ion battery cells used in electric cars. The plate is provided with Lead Film i.e. a layer of polypropylene that seals the AL. Pouch weld</p>
8529 90 92		4859170/2018	<p>Driver information display with a microprocessor-based control system:</p> <ul style="list-style-type: none"> <li>- with LED indicators for warning lights, also with a gear shift indicator and a photosensor;</li> <li>- with a glass or plastic covered and optically bonded LCD panel measuring 12 cm or more, but not more than 31 cm;</li> <li>- with LED backlighting;</li> <li>- with electronics to generate additional control indicators for vehicle information on the display;</li> <li>- with a printed circuit board with EPROM (Erasable Programmable Read-only Memory), microcontroller, timing controller and other active and passive components;</li> <li>- a plug for power supply and CAN (Controller Area Network) and LVDS</li> </ul>	S	New	UNDER EXAMINATION	DE	Applicant	<p>Round 7/2019</p> <p>The displays operate like ordinary electronic screens. They are used in motor vehicles to digitally display navigation, audio, setting and vehicle information. The displays are permanently installed in vehicles in the driver's field of vision.</p>

8529 90 92		4888648/2018	<p>(Low-Voltage Differential Signalling) interfaces;  - whether or not in a housing;  with or without a touch screen.</p> <p>LCD display suitable for mounting into cars, equipped with touch panel, printed circuit board and connector</p>	S	New	UNDER EXAMINATION	HU	Applicant	Round 7/2019 Intended use- The finished product is treated as an automatic data-processing machine for cars.
8537 10 91		4886469/2018	<p>Programmable memory control board, for a voltage 10 V or more but not more than 30 V, comprising at least:</p> <ul style="list-style-type: none"> <li>- 4 or more stepper motor drivers,</li> <li>- 4 or more outputs with MOSFET transistors,</li> <li>- main processor,</li> <li>- 3 or more inputs for temperature sensors,</li> </ul> <p>for use in the manufacture of 3D printers (2)</p>	S	New	UNDER EXAMINATION	CZ	Applicant	Round 7/2019 Intended for manufacture of 3D printers
8537 10 98		4780876/2018	<p>Electronic control units for controlling inter axle torque transferring in all-wheel drive vehicles including:</p> <ul style="list-style-type: none"> <li>- a printed circuit board,</li> <li>- a single connector, and</li> <li>- working at 12 V</li> </ul>	S	New	UNDER EXAMINATION	UK	Applicant	Round 7/2019 Part fitted to C-Pilar during bodywork assembly of motor vehicles
8537 10 98		4780964/2018	<p>Electronic control units able to control automatic continuous variable transmissions for passenger vehicles including:</p> <ul style="list-style-type: none"> <li>- printed circuit board,</li> <li>- metallic housing,</li> <li>- a single connector, and</li> <li>- working at 12 V</li> </ul>	S	New	UNDER EXAMINATION	UK	Applicant	Round 7/2019 Part fitted to the engine bay of motor vehicles

8544 19 00		1382625/2018	<p>Wire consisting of an aluminum core and a concentric copper coating which is protected by a layer of varnish that can be polyester or polyurethane; and which has the following dimensions:</p> <ul style="list-style-type: none"> <li>• a volume percentage of copper of 10 % or more but not more than 15 %</li> <li>• a diameter, excluding the varnish, of 0,14 mm or more but not more than 0,25 mm</li> </ul> <p>for winding (1)</p>	S	New		ES	Applicant	Round 7/2019 Used for electric motors for household appliances
8708 40 20		4837989/2018	<p>Transmission assembly which involves rotary switch for shift lever position Exclusively for use in the manufacture of the vehicles in heading 87,</p> <ul style="list-style-type: none"> <li>- Aluminum casting housing</li> <li>- Differential gear</li> <li>- 9 Speed automatic,</li> <li>- Electronic Range Select gear selection system,</li> <li>- With dimensions that are; 330 mm or wider but not more than 420 mm,</li> <li>- 380 mm or higher but not more than 450 mm,</li> <li>- 580 mm or longer but not more than 690 mm</li> </ul> <p>(1)</p>	S	New	UNDER EXAMINATION	TR	Applicant	Round 7/2019 For assembling and producing automobiles.
8708 40 20		4632947/2018	<p>Car transfer box, single input, dual output, to distribute torque between front and rear axles. In aluminum housing made with overall dimension not exceeding 565 x</p>	S	New	UNDER EXAMINATION	ES	Applicant	Round 7/2019 A transfer case is a part of the drivetrain of four-wheel-drive, all-wheel-

			570 x 510 mm. Comprising at least: - Actuator, - Interior distribution by chain						drive, and other multiple powered axle vehicles
8708 50 20		4765766/2018	Transmission steel shaft connecting the gearbox with semi-axle with: - a length of 300 mm or more but not more than 650 mm, - a spline end on both sides, - whether or not with a pressed bearing in the case, - whether or not with a holder for use in the manufacture of goods of Chapter 87 (1)	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 Transmission steel shaft is mounted to the front module of a passenger car.
8708 50 99		4703203/2018	Housing of tripod type halfshaft inboard joint for transmitting a torque from engine and transmission to wheels of motor vehicles: - with an outer diameter of 67,0 mm or more but not more than 84,5 mm, - with 3 cold calibrated roller tracks with a diameter of 29,90 mm or more but not more than 36,60 mm, - with sealing diameter 34,0 mm or more but not more than 41,0 mm, without lead angle, - with spline with 21 teeth or more but not more than 35, - with bearing seat diameter of 25,0 mm or more but not more than 30,0 mm, with or without oil grooves, manufactured by warm forging, machining and cold calibration methods	S	New	UNDER EXAMINATION	PL	Applicant	Round 7/2019 Housing of tripod type halfshaft inboard joint is used on the inboard side or transmission as integral part of the halfshaft that is transmitting the torque from the transmission to the wheel

8708 50 99		4702919/2018	<p>Outboard joint assembly for transmitting a torque from engine and transmission to wheels of motor vehicles, consisting of:</p> <ul style="list-style-type: none"> <li>- inner race with 6 ball tracks for running with the bearing balls with a diameter 15,0 mm or more but not more than 20,0 mm,</li> <li>- outer race with 6 ball tracks for running with 6 bearing balls, made of steel with carbon content of 0,45 % or more but not more than 0,58 %, with thread and with a spline with 26 teeth or more but not more than 38,</li> <li>- spherical cage keeping bearing balls in the ball tracks of outer race and inner race in proper angular position, made of material suitable for carburizing with carbon content of 0,14 % or more but not more than 0,25 %, and</li> <li>- with a grease compartment,</li> </ul> <p>capable of working at constant speed at variable articulation angle not higher than 50 degrees</p>	S	New	UNDER EXAMINATION	PL	Applicant	<p>Round 7/2019</p> <p>Outboard joint assembly is used on the outboard side of wheel end of the halfshaft assembly.</p>
8708 80 99		4780825/2018	<p>Aluminium suspension link arm, with dimensions of:</p> <ul style="list-style-type: none"> <li>- height of 50 mm or more but not more than 150 mm</li> <li>- width of 10 mm or more but not more than 100 mm</li> </ul>	S	New	UNDER EXAMINATION	UK	Applicant	<p>Round 7/2019</p> <p>Used in the production of motor vehicle suspension sub-assemblies</p>

			<ul style="list-style-type: none"> <li>- length of 100 mm or more but not more than 600 mm</li> <li>- mass of 1000 g or more but not more than 3000 g</li> </ul> <p>Equipped with at least two bushed holes made of aluminium alloy with the following characteristics:</p> <ul style="list-style-type: none"> <li>- tensile strength of 2000 mPa or more</li> <li>- strength of 19 kN or more</li> <li>- stiffness of 5 kN/mm or more but not more than 9 kN/mm</li> <li>- frequency of 400 Hz or more but not more than 600 Hz</li> </ul> <p>[for use in the manufacture of motor vehicles of chapter 87] (1)</p>						
8708 92 99		4784641/2018	<p>Support bracket from shaped sheet for fixing of the exhaust system:</p> <ul style="list-style-type: none"> <li>- with a wall thickness of 0,7 mm or more but not more than 1,3 mm,</li> <li>- of stainless steel class 1.4310 and 1.4301 according to norm EN 10088,</li> <li>- whether or not with mounting holes</li> </ul> <p>for use in the manufacture of exhaust systems for automobiles (1)</p>	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 After being assembled, the exhaust system will be installed to a passenger car.
8708 92 99		4785621/2018	<p>Exhaust system inner liner:</p> <ul style="list-style-type: none"> <li>- with a wall thickness of 0,7 mm or more but not more than 1,3 mm,</li> <li>- made of stainless steel class 1.4310 and 1.4301 according to norm EN 10088,</li> <li>- whether or not with mounting holes</li> </ul>	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 After being assembled, the exhaust system will be installed to a passenger car.

8708 92 99		4785712/2018	<p>for use in the manufacture of exhaust systems for automobiles (1)</p> <p>Pipe specifically shaped for guiding exhaust gases from the combustion engine:</p> <ul style="list-style-type: none"> <li>- with a diameter of 40 mm or more but not more than 100 mm,</li> <li>- with a length of 90 mm or more but not more than 410 mm,</li> <li>- with a wall thickness of 0,7 mm or more but not more than 1,3 mm,</li> <li>- of stainless steel class</li> </ul> <p>for use in the manufacture of exhaust systems for automobiles (1)</p>	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 After being assembled, the exhaust system will be installed to a passenger car.
8708 92 99		4784737/2018	<p>Exhaust system end cover:</p> <ul style="list-style-type: none"> <li>- with a wall thickness of 0,7 mm or more but not more than 1,3 mm,</li> <li>- made of stainless steel class 1.4310 and 1.4301 according to norm EN 10088,</li> <li>- whether or not with inner liner,</li> <li>- whether or not with surface treatment</li> </ul> <p>for use in the manufacture of exhaust systems for automobiles (1)</p>	S	New	UNDER EXAMINATION	SK	Applicant	Round 7/2019 Exhaust system end cover is a part of the exhaust system of a passenger car.
9002 11 00		4697914/2018	<p>Lens assembly with:</p> <ul style="list-style-type: none"> <li>- a horizontal field of view range to a</li> </ul>	S	New	UNDER	HU PL	Applicant Applicant	Round 7/2019 Intended use of the

			<p>maximum of 120 deg</p> <ul style="list-style-type: none"> <li>- a diagonal field of view range to a maximum of 92 deg</li> <li>- a focal length to a maximum of 7.50 mm</li> <li>- a relative aperture of a maximum of F/2.90</li> <li>- a maximum diameter of 22 mm</li> </ul> <p>of a kind used for the production of CMOS [complementary metal–oxide–semiconductor] automotive cameras</p>			EXAMINATION			imported product – Fully connected software platform, in conjunction with the input of cameras that classifies objects to recognize specific behaviour.
9032 89 00		4835561/2018	<p>Electronic Engine Control Unit (ECU);</p> <ul style="list-style-type: none"> <li>- with printed circuit board (PCB),</li> <li>- has 12 Volts voltage,</li> <li>- reprogrammable,</li> <li>- with micro-processor, that can control, evaluate and manage support service functions in a car (injection and ignition advance values of fuel, fuel and air flow rate)</li> </ul>	S	New	UNDER EXAMINATION	TR	Applicant	Round 7/2019 Electronic Engine Control Unit (ECU); Assembling and producing automobiles.
ex 0712 32 00 ex 0712 33 00 ex 0712 39 00	10 10 31	1617/5/1989	<p>PT – Request for amendment:</p> <p>Dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale</p> <p>Mushrooms, excluding mushrooms of the genus <i>Agaricus</i>, dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (1)(2)</p>	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 7/2019: Request for amendment
ex 2710 19 81 ex 2710 19 99	10 30	1254190/2015 3016685/2013	<p>NL- Request for amendment :</p> <p>Catalytically hydroisomerized and dewaxed base oil of hydrogenated, highly isoparaffinic hydrocarbons, containing:</p> <ul style="list-style-type: none"> <li>- 90 % or more by weight of saturates, and</li> </ul>	S	Amendment	UNDER EXAMINATION	UK	Applicant	Round 7/2019 Request for amendment



			<ul style="list-style-type: none"> <li>- not more than 0,03 % by weight of sulphur, with a viscosity index of 120 or more</li> </ul> <p>Catalytically hydroisomerized and dewaxed base oil of hydrogenated, highly isoparaffinic hydrocarbons, containing:</p> <ul style="list-style-type: none"> <li>- 90 % or more by weight of saturates, and</li> <li>- not more than 0,03 % by weight of sulphur, with a viscosity index of 80 or more</li> </ul>						
ex 2926 90 70	12	662083/2014	<p>DE Request for amendment : Cyfluthrin (ISO) (CAS RN 68359-37-5) or beta-cyfluthrin (ISO) (CAS RN 1820573-27-0) with a purity by weight of 95 % or more</p> <p>Cyfluthrin (ISO) (CAS RN 68359-37-5) with a purity by weight of 95 % or more</p>	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 7/2019 - Request for amendment.
ex 2932 13 00	20	4656805/2017	Furfuryl lcohol (CAS RN 98-00-0)	S	Amendment	UNDER EXAMINATION	UK BE	Applicant Opposed	Round 7/2019 Objection
ex 3208 90 19	20	1254133/2015	<p>DE request for amendment: Preparation of 5 % or more but not more than 20 % by weight of a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene and maleic anhydride, or a blend of polypropylene and a copolymer of propylene, isobutene and maleic</p>	S	Amendment	UNDER EXAMINATION	UK	Applicant	Round 7/2019 - Request for amendment.

			anhydride in an organic solvent						
			Preparation of 5 % or more but not more than 20 % by weight of propylene maleic anhydride copolymer or a blend of polypropylene and propylene maleic anhydride copolymer in an organic solvent						
ex 3506 91 90	60	1489313/2017	DE - Request for amendment: Temporary wafer-bonding adhesive material in the form of a suspension of a solid polymer in D-limonene (CAS RN 5989-27-5) with a polymeric content by weight of 25 % or more but not more than 35 %  Temporary wafer-bonding adhesive material in the form of a suspension of a solid polymer in D-limonene (CAS RN 5989-27-5) with a polymeric content by weight of 65 % or more but not more than 75 %	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 7/2019 - Request for amendment.
ex 3812 39 90	35	498733/2013 PROLONG 2019	UK – Request for amendment: Mixture containing by weight: - 25 % or more but not more than 55 % of a mixture of C15-18 tetramethylpiperidiny l esters (CAS RN 86403-32-9)	S	Amendment	UNDER EXAMINATION	UK	Applicant	Round 7/2019 Request for amendment

			<ul style="list-style-type: none"> <li>- not more than 20 % of other organic compounds</li> <li>- on a carrier of polypropylene (CAS RN 9003-07-0) or amorphous silica (CAS RN 7631-86-9 or 112926-00-8)</li> </ul> <p>Mixture containing by weight:</p> <ul style="list-style-type: none"> <li>- 25 % or more but not more than 50 % of a mixture of C15-18 tetramethylpiperidinyl esters (CAS RN 86403-32-9)</li> <li>- not more than 20 % of other organic compounds</li> <li>- on a carrier of polypropylene (CAS RN 9003-07-0)</li> </ul>						
ex 3815 90 90	22	1443007/2017	<p>AT - Request for amendment:</p> <p>Catalyst in powder form consisting by weight of</p> <ul style="list-style-type: none"> <li>- 92,50 % (<math>\pm</math> 2) % titanium dioxide (CAS RN 13463-67-7)</li> <li>- 5 % (<math>\pm</math> 1) % silicon dioxide (CAS RN 112926-00-8) und</li> <li>- 2,5 % (<math>\pm</math> 1,5) % sulphur trioxide (CAS RN 7446-11-9)</li> </ul> <p>Catalyst in powder form consisting by weight of 95 % (<math>\pm</math> 1 %) titanium dioxide and 5 % (<math>\pm</math> 1 %) silicon dioxide</p>	S	Amendment	UNDER EXAMINATION	AT	Applicant	Round 7/2019 - Request for amendment.
ex 3824 99 92	37	1296/2008	<p>DE- Request for amendment:</p> <p>Mixture based on 3-butene-1,2-diol diacetate (CAS RN 18085-02-4) with a content by weight of 65 % or more but not</p>	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 7/2019 - Request for amendment.

			<p>more than 90 %</p> <p>OR:</p> <p>Mixture of acetates of 3-butene-1,2-diol with a content by weight of 65 % or more</p> <p>Mixture of acetates of 3-butylene-1,2-diol with a content by weight of 65 % or more but not more than 90 %</p>						
ex 3905 91 00	40	1048299/2012	<p>DE - Request for amendment: Copolymer of ethylene and vinyl alcohol (CAS RN 26221-27-2), containing by weight not more than 38 % of the monomer unit ethylene</p> <p>Water soluble copolymer of ethylene and vinyl alcohol (CAS RN 26221-27-2), containing by weight not more than 38 % of the monomer unit ethylene</p>	S	Amendment	UNDER EXAMINATION	DE	Applicant	Round 7/2019 - Request for amendment.
ex 3907 20 20	40	921/05	<p>UK – Request for amendment : Copolymer of tetrahydrofuran and tetrahydro-3-methylfuran with a number average molecular weight (Mn) of 1 000 or more but not more than 3 500 (± 100)</p> <p>Copolymer of tetrahydrofuran and tetrahydro-3-methylfuran with a number</p>	S	Amendment	UNDER EXAMINATION	UK NL	Applicant Co-applicant	Round 7/2019 - Request for amendment.

ex 3923 10 90	10	1010631/2011	<p>average molecular weight (<math>M_n</math>) of 3 500 (<math>\pm</math> 100)</p> <p>Photomask or wafer compacts:</p> <ul style="list-style-type: none"> <li>- consisting of antistatic materials or blended thermoplastics proving special electrostatic discharge (ESD) and outgassing properties,</li> <li>- having non porous, abrasion resistant or impact resistant surface properties,</li> <li>- fitted with a specially designed retainer system that protects the photomask or wafers from surface or cosmetic damage and</li> <li>- with or without a gasket seal,</li> </ul> <p>of a kind used in the photolithography or other semiconductor production to house photomasks or wafers</p>	S	Amendment	UNDER EXAMINATION	UK	Applicant	Round 7/2019 Proposal to remove the code due to the fact that CN code 3923 10 10 as duty free also covers goods defined into the TARIC line
ex 8482 10 10 ex 8482 10 90	40 30	847423/2014	<p>Ball bearings:</p> <ul style="list-style-type: none"> <li>- with an internal diameter of 3 mm or more,</li> <li>- with an external diameter of not more than 100 mm,</li> <li>- with a width of not more than 40 mm,</li> <li>- whether or not equipped with a duster,</li> </ul> <p>for use in the manufacture of belt drive steering systems of motor, electric power steering systems or steering gears or assembly ball screw for steering gears (1)</p>	S	Amendment	UNDER EXAMINATION	SK TR	Applicant Opposed	Round 7/2019: Objection
ex 8501 31 00 8501 32 00	55	371604/2013 PROLONG 2019	<p>HU – Request for amendment:</p> <p>DC motor with or without commutator, with</p> <ul style="list-style-type: none"> <li>- an external diameter of 24,2 mm or more, but not more than 140 mm,</li> <li>- a rated speed of 3300 rpm or more,</li> </ul>	S	Amendment	UNDER EXAMINATION	HU	Applicant	Round 7/2019 Request for amendment

			<p>but not more than 26200 rpm,</p> <ul style="list-style-type: none"> <li>- a rated supply voltage of 3,6 V or more, but not more than 230 V,</li> <li>- an output power of 37,5 W or more, but not more than 2400 W,</li> <li>- a free load current of not more than 20,1 A,</li> <li>- a maximum efficiency of 50 % or more,</li> </ul> <p>for driving hand-held power tools or lawn mowers</p> <p>Current description</p> <p>DC motor with commutator, with</p> <ul style="list-style-type: none"> <li>- an external diameter of 27.5 mm or more, but not more than 45 mm,</li> <li>- a rated speed of 11 000 rpm or more, but not more than 23 200 rpm,</li> <li>- a rated supply voltage of 3.6 V or more, but not more than 230 V,</li> <li>- an output power of not more than 529 W,</li> <li>- a free load current of not more than 3.1 A,</li> <li>- a maximum efficiency of 54 % or more,</li> </ul> <p>for driving hand-held power tools</p>						
ex 8481 80 59	30	4629095/2017	<p>HU - Request for amendment:</p> <p>Two-way flow control valve with housing, with:</p> <ul style="list-style-type: none"> <li>- at least 5, but not more than 10 outlet holes with at least 0,09 mm, but not more than 0,2 mm diameter,</li> <li>- at least 550 cm<sup>3</sup>/minute, but not more than 2000 cm<sup>3</sup>/minute flow rate,</li> <li>- at least 19, but not more than 300 MPa operating pressure</li> </ul>	S	Amendment	UNDER EXAMINATION	HU	Applicant	ROUND 07/2019: Request for amendment

			<p>Two-way flow control valve with housing, with</p> <ul style="list-style-type: none"> <li>- at least 5 but not more than 9 outlet holes with at least 0,110 mm but not more than 0,134 mm diameter,</li> <li>- at least 640 cm<sup>3</sup> / minute but not more than 805 cm<sup>3</sup> / minute flow rate,</li> <li>- at least 19 but not more than 300 MPa operating pressure</li> </ul>						
ex 8481 80 59	40	4629031/2017	<p>HU – Request for amendment:</p> <p>Flow-control valve</p> <ul style="list-style-type: none"> <li>- made of steel,</li> <li>- with an outlet hole with a diameter of at least 0,1 mm, but not more than 0,3 mm,</li> <li>- with an inlet hole with a diameter of at least 0,4 mm, but not more than 1,3 mm,</li> <li>- with chromium nitride coating,</li> <li>- with a surface roughness of Rp 0,4</li> </ul> <p>Flow-control valve</p> <ul style="list-style-type: none"> <li>- made of steel,</li> <li>- with an outlet hole with a diameter of at least 0,175 mm, but not more than 0,185 mm,</li> <li>- with an inlet hole with a diameter of at least 0,255 mm, but not more than 0,265 mm,</li> <li>- with chromium nitride coating,</li> <li>- with a surface roughness of Rp 0,4</li> </ul>	S	Amendment	UNDER EXAMINATION	HU	Applicant	ROUND 07/2019: request for amendment
ex 8481 80 59	50	4629114/2017	<p>HU – Request for amendment:</p> <p>Electromagnetic valve for quantity control with</p> <ul style="list-style-type: none"> <li>- a plunger,</li> </ul>	S	Amendment	UNDER EXAMINATION	HU	Applicant	ROUND 07/2019: request for amendment

ex 8481 80 59	60	4629063/2017	<ul style="list-style-type: none"> <li>- a solenoid with a of coil resistance of at least 2,6 Ohm, but not more than 3 Ohm</li> </ul> <p>Electromagnetic valve for quantity control with</p> <ul style="list-style-type: none"> <li>- a plunger,</li> <li>- DLC (Diamond-like carbon) coating,</li> <li>- a solenoid with a of coil resistance of at least 2,6 Ohm, but not more than 3 Ohm,</li> <li>- a supply voltage of 12 V</li> </ul> <p>HU – Request for amed amended description: Electromagnetic valve for quantity control</p> <ul style="list-style-type: none"> <li>- with a solenoid with a coil resistance of at least 0,19 Ohm, but not more than 0,66 Omh, and with an inductance of not more than 1 mH</li> </ul> <p>Electromagnetic valve for quantity control</p> <ul style="list-style-type: none"> <li>- with a solenoid with a coil resistance of at least 0,19 Ohm, but not more than 0,52 Omh, and with an inductance of at least 0,083 mH, but not more than 0,172 mH,</li> <li>- with a supply voltage of 24 V,</li> <li>- operating at a DC of at least 15,5 A, but not more than 16,5 A</li> </ul>	S	Amendment	UNDER EXAMINATION	HU	Applicant	ROUND 07/2019: request for amendment
ex 8501 32 00 ex 8501 33 00	60 15	3104160/2014	<p>UK - Request for amendment: AC traction motor of an output of 75kW but not exceeding 375kW, with:</p> <ul style="list-style-type: none"> <li>- a torque output of 200 Nm or more but not more than 300 Nm</li> <li>- a power output of 50 kW or more</li> </ul>	S	Amendment	UNDER EXAMINATION	UK	Applicant	Round 7/2019 - Request for amendment.



			<p>but not more than 100 kW, and</p> <ul style="list-style-type: none"> <li>- a speed of not more than 15 000 rpm</li> </ul> <p>for use in the manufacture of electric vehicles</p> <p>(1)</p> <p>Traction motor, with:</p> <ul style="list-style-type: none"> <li>- a torque output of 200 Nm or more but not more than 300 Nm</li> <li>- a power output of 50 kW or more but not more than 100 kW</li> <li>- a rated speed of not more than 12 500 rpm</li> </ul> <p>for use in the manufacture of electric vehicles</p> <p>(1)</p>						
ex 8507 60 00	33	1232310/2015	<p>HU – Request for amendment:</p> <p>Lithium-ion accumulator, with:</p> <ul style="list-style-type: none"> <li>- a length of 150 mm or more, but not more than 1 000 mm</li> <li>- a width of 400 mm or more, but not more than 1 000 mm</li> <li>- a height of 200 mm or more, but not more than 1 500 mm</li> <li>- a weight of 75 kg or more, but not more than 200 kg</li> <li>- a nominal capacity not less than 150 Ah and not more than 500 Ah</li> </ul> <p>Lithium-ion accumulator, with:</p> <ul style="list-style-type: none"> <li>- a length of 150 mm or more, but not more than 300 mm</li> <li>- a width of 700 mm or more, but not more than 1 000 mm</li> <li>- a height of 1 100 mm or more, but not more than 1 500 mm</li> <li>- a weight of 75 kg or more, but not more than 160 kg</li> </ul>	S	Amendment	UNDER EXAMINATION	NL	Applicant	ROUND 7/2019: Request for amendment

ex 8529 90 65	15	1144223/2015	<p>- a nominal capacity not less than 150 Ah and not more than 500 Ah</p> <p>PT - Request for amendment: Electronic assembly comprising at least</p> <ul style="list-style-type: none"> <li>- a printed circuit board with,</li> <li>- processors for multi-media applications and video signal processing,</li> <li>- FPGA (Field Programmable Gate Array),</li> <li>- Flash memory,</li> <li>- operating memory,</li> <li>- USB-interface,</li> <li>- with or without HDMI, VGA- and RJ-45 interfaces,</li> <li>- sockets and plugs for connecting a LCD-display, a LED-backlight and a control panel</li> </ul> <p>Electronic assembly comprising at least</p> <ul style="list-style-type: none"> <li>- a printed circuit</li> <li>- processors for multi-media applications and video signal processing</li> <li>- FPGA (Field Programmable Gate Array)</li> <li>- Flash memory</li> <li>- operating memory</li> <li>- HDMI, VGA, USB and RJ-45 interfaces</li> <li>- sockets and plugs for connecting a LCD-monitor, a LED lighting and a control panel</li> </ul>	S	Amendment	UNDER EXAMINATION	AT	Applicant	ROUND 7/2019: Request for amendment
ex 9029 20 31 ex 9029 90 00	10 20	3033673/2014	<p>PT – Request for amendment: Clustered instrument panel with the microprocessor control board, with or without stepping motors, and LED</p>	S	Amendment	UNDER EXAMINATION	SK	Applicant	Round 7/2019 Request for amendment

